

**SAFETY DATA SHEET**  
NANOLEX URBAN GLASS SEALANT

Page: 1

Compilation date: 21.03.2017

Revision No: 1

**Section 1: Identification of the substance/mixture and of the company/undertaking**

**1.1. Product identifier**

**Product name:** NANOLEX URBAN GLASS SEALANT

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

**Use of substance / mixture:** PC9a: Coatings and paints, thinners, paint removers.

**1.3. Details of the supplier of the safety data sheet**

**Company name:** Infinitec Gmbh

Taubfeld 18

Saarbrücken

D-66121

Germany

**Tel:** +4968198 800306

**Email:** [a.neuner@infinitec-gmbh.de](mailto:a.neuner@infinitec-gmbh.de)

**1.4. Emergency telephone number**

**Emergency tel:** Medical Emergency information in case of poisoning: Poison Information Center Mainz -  
24h - Phone: +49 (0) 6131 19240 (advisory service in German or English language)

**Section 2: Hazards identification**

**2.1. Classification of the substance or mixture**

**Classification under CLP:** Asp. Tox. 1: H304; Aquatic Chronic 3: H412; Flam. Liq. 3: H226; Skin Corr. 1A: H314

**Most important adverse effects:** Flammable liquid and vapour. May be fatal if swallowed and enters airways. Causes severe skin burns and eye damage. Harmful to aquatic life with long lasting effects.

**2.2. Label elements**

**Label elements:**

**Hazard statements:** H226: Flammable liquid and vapour.

H304: May be fatal if swallowed and enters airways.

H314: Causes severe skin burns and eye damage.

H412: Harmful to aquatic life with long lasting effects.

**Hazard pictograms:** GHS02: Flame

GHS05: Corrosion

GHS08: Health hazard



**Signal words:** Danger

[cont...]

# SAFETY DATA SHEET

## NANOLEX URBAN GLASS SEALANT

Page: 2

**Precautionary statements:** P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P241: Use explosion-proof electrical/ventilating/lighting/.. equipment.  
P260: Do not breathe dust/fumes/gas/mist/vapours/spray.  
P280: Wear protective gloves/protective clothing/eye protection/face protection.  
P301+310: IF SWALLOWED: Immediately call a POISON CENTER/doctor.  
P301+330+331: IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

### 2.3. Other hazards

**Other hazards:** In use, may form flammable / explosive vapour-air mixture.

**PBT:** This product is not identified as a PBT/vPvB substance.

## Section 3: Composition/information on ingredients

### 3.2. Mixtures

#### Hazardous ingredients:

HYDROCARBONS, C4,1,3-BUTADIENE-FREE, POLYMD., TRIISOBUTYLENE FRACTION, HYDROGENATED

EINECS	CAS	PBT / WEL	CLP Classification	Percent
-	93685-81-5	-	Flam. Liq. 3: H226; Asp. Tox. 1: H304; Aquatic Chronic 4: H413	10-30%

HYDROCARBONS, C10-C12, ISO ALKANES, <2% AROMATICS

EINECS	CAS	PBT / WEL	CLP Classification	Percent
-	923-037-2	-	Flam. Liq. 3: H226; Asp. Tox. 1: H304; Aquatic Chronic 2: H411	1-10%

SULPHURIC ACID

EINECS	CAS	PBT / WEL	CLP Classification	Percent
231-639-5	7664-93-9	-	Skin Corr. 1A: H314	1-10%

## Section 4: First aid measures

### 4.1. Description of first aid measures

**Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin.

Drench the affected skin with running water for 10 minutes or longer if substance is still on skin. Transfer to hospital if there are burns or symptoms of poisoning.

**Eye contact:** Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.

**Ingestion:** Wash out mouth with water. Do not induce vomiting. Give 1 cup of water to drink every 10 minutes. If unconscious, check for breathing and apply artificial respiration if necessary. If unconscious and breathing is OK, place in the recovery position. Transfer to hospital as soon as possible.

**Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. If unconscious and breathing is OK, place in the recovery position. If conscious, ensure the casualty sits or lies down. If breathing becomes bubbly, have the casualty sit and provide oxygen if available. Transfer to hospital as soon as possible.

[cont...]

# SAFETY DATA SHEET

## NANOLEX URBAN GLASS SEALANT

Page: 3

### 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** Blistering may occur. Progressive ulceration will occur if treatment is not immediate.

**Eye contact:** Corneal burns may occur. May cause permanent damage.

**Ingestion:** Corrosive burns may appear around the lips. Blood may be vomited. There may be bleeding from the mouth or nose.

**Inhalation:** There may be shortness of breath with a burning sensation in the throat. Exposure may cause coughing or wheezing.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

### 4.3. Indication of any immediate medical attention and special treatment needed

**Immediate / special treatment:** Eye bathing equipment should be available on the premises.

## Section 5: Fire-fighting measures

### 5.1. Extinguishing media

**Extinguishing media:** Water spray. Carbon dioxide. Dry chemical powder. Alcohol resistant foam.

### 5.2. Special hazards arising from the substance or mixture

**Exposure hazards:** Corrosive. In combustion emits toxic fumes. Highly flammable. Vapour may travel considerable distance to source of ignition and flash back. Forms explosive air-vapour mixture.

### 5.3. Advice for fire-fighters

**Advice for fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

## Section 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions:** Notify the police and fire brigade immediately. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Turn leaking containers leak-side up to prevent the escape of liquid. Refer to section 8 of SDS for personal protection details. Eliminate all sources of ignition.

### 6.2. Environmental precautions

**Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using bunding.

### 6.3. Methods and material for containment and cleaning up

**Clean-up procedures:** Clean-up should be dealt with only by qualified personnel familiar with the specific substance. Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Do not use equipment in clean-up procedure which may produce sparks.

[cont...]

**SAFETY DATA SHEET**  
NANOLEX URBAN GLASS SEALANT

Page: 4

**6.4. Reference to other sections**

**Reference to other sections:** Refer to section 8 of SDS.

**Section 7: Handling and storage**

**7.1. Precautions for safe handling**

**Handling requirements:** Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.  
Do not handle in a confined space. Avoid the formation or spread of mists in the air.  
Smoking is forbidden. Use non-sparking tools.

**7.2. Conditions for safe storage, including any incompatibilities**

**Storage conditions:** Store in a cool, well ventilated area. Keep container tightly closed.

**7.3. Specific end use(s)**

**Specific end use(s):** No data available.

**Section 8: Exposure controls/personal protection**

**8.1. Control parameters**

**Hazardous ingredients:**

**SULPHURIC ACID...100%**

**Workplace exposure limits:**

**Respirable dust**

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	0.05 mg/m <sup>3</sup>	-	-	-

**DNEL/PNEC Values**

**DNEL / PNEC** No data available.

**8.2. Exposure controls**

**Engineering measures:** Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not a source of ignition.

**Respiratory protection:** Self-contained breathing apparatus must be available in case of emergency.

**Hand protection:** Impermeable gloves.

**Eye protection:** Tightly fitting safety goggles. Ensure eye bath is to hand.

**Skin protection:** Impermeable protective clothing.

**Environmental:** The floor of the storage room must be impermeable to prevent the escape of liquids.

**Section 9: Physical and chemical properties**

**9.1. Information on basic physical and chemical properties**

**State:** Liquid

**Colour:** White

**Odour:** Characteristic odour

[cont...]

**SAFETY DATA SHEET**  
NANOLEX URBAN GLASS SEALANT

Page: 5

**Viscosity:** Non-viscous  
**Boiling point/range°C:** 100  
**Relative density:** 0,92

**Flash point°C:** 31  
**pH:** 2

**9.2. Other information**

**Other information:** No data available.

**Section 10: Stability and reactivity**

**10.1. Reactivity**

**Reactivity:** Stable under recommended transport or storage conditions.

**10.2. Chemical stability**

**Chemical stability:** Stable under normal conditions. Stable at room temperature.

**10.3. Possibility of hazardous reactions**

**Hazardous reactions:** Hazardous reactions will not occur under normal transport or storage conditions.  
Decomposition may occur on exposure to conditions or materials listed below.

**10.4. Conditions to avoid**

**Conditions to avoid:** Heat. Hot surfaces. Sources of ignition. Flames.

**10.5. Incompatible materials**

**Materials to avoid:** Strong oxidising agents. Strong acids.

**10.6. Hazardous decomposition products**

**Haz. decomp. products:** In combustion emits toxic fumes.

**Section 11: Toxicological information**

**11.1. Information on toxicological effects**

**Hazardous ingredients:**

**HYDROCARBONS, C4,1,3-BUTADIENE-FREE, POLYMD., TRIISOBUTYLENE FRACTION, HYDROGENATED**

DERMAL	RAT	LD50	>5000	mg/kg
ORAL	RAT	LD50	>15000	mg/kg

**HYDROCARBONS, C10-C12, ISO ALKANES, <2% AROMATICS**

DERMAL	RBT	LD50	>5000	mg/kg
ORAL	RAT	LD50	>5000	mg/kg

**SULPHURIC ACID...100%**

ORL	RAT	LD50	2140	mg/kg
-----	-----	------	------	-------

[cont...]

**SAFETY DATA SHEET**  
**NANOLEX URBAN GLASS SEALANT**

Page: 6

**Relevant hazards for product:**

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated
Aspiration hazard	-	Hazardous: calculated

**Symptoms / routes of exposure**

**Skin contact:** Blistering may occur. Progressive ulceration will occur if treatment is not immediate.

**Eye contact:** Corneal burns may occur. May cause permanent damage.

**Ingestion:** Corrosive burns may appear around the lips. Blood may be vomited. There may be bleeding from the mouth or nose.

**Inhalation:** There may be shortness of breath with a burning sensation in the throat. Exposure may cause coughing or wheezing.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

**Section 12: Ecological information**

**12.1. Toxicity**

**Hazardous ingredients:**

**HYDROCARBONS, C4,1,3-BUTADIENE-FREE, POLYMD., TRIISOBUTYLENE FRACTION, HYDROGENATED**

Daphnia magna	48H EC50	>0,04	mg/l
---------------	----------	-------	------

**HYDROCARBONS, C10-C12, ISO ALKANES, <2% AROMATICS**

Daphnia magna	48H EC50	1000	mg/l
RAINBOW TROUT ( <i>Oncorhynchus mykiss</i> )	96H LC50	1000	mg/l

**12.2. Persistence and degradability**

**Persistence and degradability:** Biodegradable.

**12.3. Bioaccumulative potential**

**Bioaccumulative potential:** No bioaccumulation potential.

**12.4. Mobility in soil**

**Mobility:** Readily absorbed into soil.

**12.5. Results of PBT and vPvB assessment**

**PBT identification:** This product is not identified as a PBT/vPvB substance.

**12.6. Other adverse effects**

**Other adverse effects:** Negligible ecotoxicity.

[cont...]

**SAFETY DATA SHEET**  
NANOLEX URBAN GLASS SEALANT

Page: 7

**Section 13: Disposal considerations**

**13.1. Waste treatment methods**

**Disposal operations:** Transfer to a suitable container and arrange for collection by specialised disposal company.

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

**Section 14: Transport information**

**14.1. UN number**

**UN number:** UN2924

**14.2. UN proper shipping name**

**Shipping name:** Flammable liquid, corrosive, n.o.s.  
(Isodecane, Isoundecane, sulphuric acid.)

**14.3. Transport hazard class(es)**

**Transport class:** III

**14.4. Packing group**

**Packing group:** 3

**14.5. Environmental hazards**

**Environmentally hazardous:** No

**Marine pollutant:** No

**14.6. Special precautions for user**

**Special precautions:** No special precautions.

**Section 15: Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**Specific regulations:** Not applicable.

**15.2. Chemical Safety Assessment**

**Chemical safety assessment:** A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

**Section 16: Other information**

**Other information**

**Other information:** This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830.

\* indicates text in the SDS which has changed since the last revision.

**Phrases used in s.2 and s.3:** H226: Flammable liquid and vapour.

H304: May be fatal if swallowed and enters airways.

[cont...]

**SAFETY DATA SHEET**  
NANOLEX URBAN GLASS SEALANT

**Page: 8**

H314: Causes severe skin burns and eye damage.

H411: Toxic to aquatic life with long lasting effects.

H412: Harmful to aquatic life with long lasting effects.

H413: May cause long lasting harmful effects to aquatic life.

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.