

auto-foam

active snow foam

Product Function:

Auto-foam is a powerful cleaner designed to remove heavy soils and contaminants from automotive surfaces. This is a non-caustic product that will not dull high gloss finishes even with frequent concentrated use. Cleaners containing sodium hydroxide can lead to paint film destruction - auto-foam is free of this material. Auto-foam is a rapid wet product, as such, the requirement for high build clinging foams is obviated. While a complete foam blanket can be obtained it is the rapid breaking of the accumulated bubbles that allows the surfactants to continue wetting out and removing soil as the applied product moves from the vehicle. Auto-foam meets all EU biodegradability requirements.

How to Use:

Use on cool surfaces. Dilute product as required to reach a PIR (Panel Impact Ratio) of 1 part in 100 for light cleaning and up to 5 parts in one hundred for heavily soiled vehicles. It is important to know the flow rate of your equipment to determine the correct add rate. If in doubt measure the nozzle output and chemical feed rate.

Health & Safety

Keep material away from children. Avoid prolonged skin contact, wash from skin or eyes with copious quantities of clean water immediately. Do not ingest.

BILT-HAMBER laboratories
Radford way
Billericay
Essex
CM12 0EG

T: +44 (0) 1277 658899
F: +44 (0) 1277 657533
E: enquiries@bilthamber.com