

## How To Use Nanolex Final Finish

This product can be stored for up to 24 months (in a dry, temperature stable environment)

### Consumption:


appr. 2ml/m<sup>2</sup>

**Processing temperature:** 5-30°C - Avoid direct sunlight and/or high air humidity.

IMPORTANT: Before you use a Nanolex Car Care product please make sure you wear suitable protection gear – we always recommend to use Latex- or Nitril gloves to make sure your hands are protected from any possible damage to your skin.

1. Spread approx. 1 – 2 ml of Nanolex Final Finish on a soft microfiber cloth pad and apply it sparingly to paint / glass / rims / plastic surfaces by rubbing in with very light pressure and permanent circular movements.
2. Avoid water contact for at least 15 minutes after the application of Nanolex Final Finish was completed.

If you have any questions regarding our products or in case you need support during the application please feel free to get in touch with our staff any time.



The information on this data sheet is based on the current status of technical development as well as our experience with the product. However, given the variety of surfaces and ambient conditions, the information provided on this data sheet shall in no way diminish the responsibility of the user to ensure with due care, that our product is suited for the intended purpose, surface and application conditions. Since application and processing lie outside our purview, no manufacturer liability shall be derived from the information provided herein. Our General Terms and Conditions of business shall apply in all cases. All information is subject to change without notice.