

# EXTRA GLOSS PROTECTION

Page: 1

Compilation date: 05/10/2004

Revision date: 23/04/2015

Revision No: 12

# Section 1: Identification of the substance/mixture and of the company/undertaking

## 1.1. Product identifier

# Product name: EXTRA GLOSS PROTECTION

Product code: No.1/SOL/5103

# 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Polish for use on motor vehicle bodies

# 1.3. Details of the supplier of the safety data sheet

Company name: AUTOGLYM

|        | Works Road          |  |  |
|--------|---------------------|--|--|
|        | Letchworth          |  |  |
|        | Herts               |  |  |
|        | SG6 1LU             |  |  |
|        | UK                  |  |  |
| Tel:   | +44 (0) 1462 677766 |  |  |
| Fax:   | +44 (0) 1462 677712 |  |  |
| Email: | sds@autoglym.co.uk  |  |  |

# 1.4. Emergency telephone number

Emergency tel: +44 (0) 1462 489498 (24Hrs)

# Section 2: Hazards identification

## 2.1. Classification of the substance or mixture

| Classification under CLP:       | STOT SE 3: H336; Asp. Tox. 1: H304; Flam. Liq. 3: H226                               |
|---------------------------------|--|
| Classification under CHIP:      | -: R10; Xn: R65; -: R66; -: R67  |
| Most important adverse effects: | Flammable liquid and vapour. May be fatal if swallowed and enters airways. May cause |
|                                 | drowsiness or dizziness.   |

#### 2.2. Label elements

| Label elements:    |   |  |  |
|--------------------|---|--|--|
| Hazard statements: | : * H226: Flammable liquid and vapour.              |  |  |
|                    | H304: May be fatal if swallowed and enters airways. |  |  |
|                    | H336: May cause drowsiness or dizziness.            |  |  |
| Signal words:      | * Danger  |  |  |
| Hazard pictograms: | * GHS02: Flame                                      |  |  |
|                    | GHS07: Exclamation mark                             |  |  |
|                    | GHS08: Health hazard                                |  |  |

EXTRA GLOSS PROTECTION



| Precautionary statements: | * P102: Keep out of reach of children.   |
|---------------------------|--|
|                           | P301+310: IF SWALLOWED: Immediately call a.  |
|                           | P331: Do NOT induce vomiting.  |
|                           | P405: Store locked up.   |
|                           | P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition      |
|                           | sources. No smoking.   |
|                           | P304+340: IF INHALED: Remove person to fresh air and keep comfortable for breathing. |
|                           | P261: Avoid breathing vapours.   |
|                           |  |

### 2.3. Other hazards

Other hazards: In use, may form flammable / explosive vapour-air mixture.

**PBT:** This product is not identified as a PBT/vPvB substance.

## Section 3: Composition/information on ingredients

# 3.2. Mixtures

### Hazardous ingredients:

#### NAPTHA (PETROLEUM) HYDROTREATED HEAVY

| EINECS   | CAS   | CHIP Classification | CLP Classification   | Percent |  |
|--|---|---------------------|--|---------|--|
| 265-150-3  | 64742-48-9 - Flam. Liq. 3: H226; STOT SE 3: H336;<br>Asp. Tox. 1: H304; -: EUH066 |                     | Flam. Liq. 3: H226; STOT SE 3: H336;<br>Asp. Tox. 1: H304; -: EUH066 | 30-50%  |  |
| LOW BOILING POINT HYDROGEN TREATED NAPHTHA - NAPHTHA (PETROLEUM), HYDROTREATED HEAVY |   |                     |  |         |  |
| 265-150-3  | 64742-48-9  | -                   | Asp. Tox. 1: H304; Flam. Liq. 3: H226                                | 30-50%  |  |

# Section 4: First aid measures

#### 4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin.

Drench the affected skin with running water for 10 minutes or longer if substance is still on skin. Consult a doctor.

- **Eye contact:** Bathe the eye with running water for 15 minutes. Consult a doctor.
- **Ingestion:** Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water to drink immediately. Consult a doctor.
- Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

## 4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Page: 2

## EXTRA GLOSS PROTECTION

Page: 3

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach

pain may occur. There may be vomiting.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

### 4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

## Section 5: Fire-fighting measures

5.1. Extinguishing media

**Extinguishing media:** Alcohol or polymer foam. Carbon dioxide. Dry chemical powder. Use water spray to cool containers.

#### 5.2. Special hazards arising from the substance or mixture

Exposure hazards: Flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture.

#### 5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

# Section 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions:** Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid. Eliminate all sources of ignition.

### 6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

#### 6.3. Methods and material for containment and cleaning up

**Clean-up procedures:** Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Do not use equipment in clean-up procedure which may produce sparks. Refer to section 13 of SDS for disposal considerations.

#### 6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

### Section 7: Handling and storage

### 7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

Do not handle in a confined space. Avoid the formation or spread of mists in the air.

Smoking is forbidden. Use non-sparking tools.

### EXTRA GLOSS PROTECTION

#### 7.2. Conditions for safe storage, including any incompatibilities

**Storage conditions:** Store in a cool, well ventilated area. Keep container tightly closed. Keep away from

sources of ignition. Prevent the build up of electrostatic charge in the immediate area.

Ensure lighting and electrical equipment are not a source of ignition.

#### 7.3. Specific end use(s)

Specific end use(s): No data available.

### Section 8: Exposure controls/personal protection

8.1. Control parameters

Workplace exposure limits: Not applicable.

## 8.2. Exposure controls

Engineering measures:Ensure there is sufficient ventilation of the area. Ensure lighting and electrical<br/>equipment are not a source of ignition.Respiratory protection:Self-contained breathing apparatus must be available in case of emergency.Hand protection:Nitrile gloves. Breakthrough time of the glove material > 8 hours.Eye protection:Safety glasses. Ensure eye bath is to hand.Skin protection:Impermeable protective clothing.

#### Section 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

| State:                        | Liquid  |                          |                    |
|-------------------------------|---|--------------------------|--------------------|
| Colour:                       | Beige   |                          |                    |
| Odour:                        | Characteristic odour                              |                          |                    |
| Evaporation rate:             | No data available.                                |                          |                    |
| Oxidising:                    | No data available.                                |                          |                    |
| Solubility in water:          | Not miscible                                      |                          |                    |
| Viscosity:                    | Non-viscous                                       |                          |                    |
| Viscosity test method:        | Flow time in seconds in a 3 mm ISO cup (ISO 2431) |                          |                    |
| Boiling point/range°C:        | 150   | Melting point/range°C:   | No data available. |
| Flammability limits %: lower: | No data available.                                | upper:                   | No data available. |
| Flash point°C:                | 36 <b>Part</b>                                    | .coeff. n-octanol/water: | No data available. |
| Autoflammability°C:           | No data available.                                | Vapour pressure:         | No data available. |
| Relative density:             | 0.775 - 0.790                                     | pH:                      | Not applicable.    |
| VOC g/l:                      | No data available.                                |                          |                    |

9.2. Other information

Section 10: Stability and reactivity

## EXTRA GLOSS PROTECTION

### 10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

## 10.2. Chemical stability

Chemical stability: Stable under normal conditions. Stable at room temperature.

#### 10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

## 10.4. Conditions to avoid

Conditions to avoid: Heat. Hot surfaces. Sources of ignition. Flames.

# 10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

## 10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

# Section 11: Toxicological information

#### 11.1. Information on toxicological effects

Toxicity values: Not applicable.

## Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach

pain may occur. There may be vomiting.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

## Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: Not applicable.

# 12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

### 12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

**PBT identification:** This product is not identified as a PBT/vPvB substance.

### EXTRA GLOSS PROTECTION

Page: 6

#### 12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

## Section 13: Disposal considerations

#### 13.1. Waste treatment methods

Waste code number: 140603

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1263

14.2. UN proper shipping name

#### Shipping name: PAINT RELATED MATERIAL

(LOW BOILING POINT HYDROGEN TREATED NAPHTHA - NAPHTHA (PETROLEUM),

#### HYDROTREATED HEAVY)

14.3. Transport hazard class(es)

Transport class: 3

14.4. Packing group

Packing group: III

14.5. Environmental hazards

Environmentally hazardous: No

Marine pollutant: Yes

#### 14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D/E

Transport category: 3

### Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture

by the supplier.

# Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

2015/830.

# EXTRA GLOSS PROTECTION

Phrases used in s.2 and s.3:EUH066: Repeated exposure may cause skin dryness or cracking.H226: Flammable liquid and vapour.H304: May be fatal if swallowed and enters airways.H336: May cause drowsiness or dizziness.H340: May cause genetic defects <state route of exposure if it is conclusively proven that</td>no other routes of exposure cause the hazard>.H350: May cause cancer <state route of exposure if it is conclusively proven that no other</td>routes of exposure cause the hazard>.H10: Flammable.R10: Flammable.R65: Harmful: may cause lung damage if swallowed.R66: Repeated exposure may cause skin dryness or cracking.R67: Vapours may cause drowsiness and dizziness.Legal disclaimer:The above information is believed to be correct but does not purport to be all inclusive<br/>and shall be used only as a guide. This company shall not be held liable for any<br/>damage resulting from handling or from contact with the above product.