

Revision Number 1 Compilation date: 02/06/15

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/ MIXTURE OF THE COMPANY/ UNDERTAKING

1.1 Product Identifier

Product name: air con bomb - CITRUS

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses: Air conditioning system deoderiser

1.3.Details of the supplier of the safety data sheet

Company name and address:

Bilt Hamber Laboratories Radford Way,

Billericay, Essex, CM12 0EG United Kingdom

Tel: 01277 658899

Email: sales@bilthamber.com

1.4.Emergency telephone number

01277 658899 (office hours only)

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Classification under CLP: Aquatic Chronic 3: H412; Flam. Aerosol 1: H222; -: H229

Most important adverse effects: Extremely flammable aerosol. Pressurised container: May burst if heated.

Harmful to aquatic life with long lasting effects.

2.2. Label elements

Hazard statements: H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated H412: Harmful to aquatic life with long lasting effects.

Hazard pictograms: GHS02: Flame

Signal words: Danger

Precautionary statements: P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211: Do not spray on an open flame or other ignition source.

P251: Do not pierce or burn, even after use.

P261: Avoid breathing spray.

P410+412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C. P501: Dispose of contents/container to hazardous or special waste collection point.

2.3 Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

ETHANOL - REACH registered number(s): 01-2119457610-43

EINECS	CAS	PBT/WEL	CLP Classification	Percent
200-578-6	64-17-5	Substance with a Community workplace exposure limit.	Flam. Liq. 2: H225	30- 50%

BUTANE

203-448-7 106	16-97-8	Substance with a Community workplace exposure limit.	Flam. Gas 1: H220; Press. Gas: H280	10- 30%
---------------	---------	---------------------------------------------------------	-------------------------------------	------------



Revision Number 1 Compilation date: 02/06/15

PROPANE

200-827-9	74-98-6	Substance with a Community workplace exposure limit.	Flam. Gas 1: H220; Press. Gas: H280	10- 30%
SOBUTANE		,		
200-857-2	75-28-5	Substance with a Community workplace exposure limit.	Flam. Gas 1: H220; Press. Gas: H280	10- 30%
3-IODO-2-PROPY	NYL BUTYLCARBAMA	ΓE		
259-627-5	55406-53-6	-	Acute Tox. 3: H331; Acute Tox. 4: H302; STOT RE 1: H372; Eye Dam. 1: H318; Skin Sens. 1: H317; Aquatic Chronic 1: H410; Aquatic Acute 1: H400	<1%

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with

plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Do not induce vomiting. Wash out mouth with water. If conscious, give half a litre of water to drink

immediately. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. If conscious, ensure the

casualty sits or lies down. Move to fresh air in case of accidental inhalation of vapours. Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be difficulty swallowing. Headaches or general malaise may result. There may be vomiting and

diarrhoea. The casualty may appear

intoxicated. There may be loss of consciousness.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing

or wheezing. Drowsiness or mental confusion may occur. There may be loss of consciousness.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention or special treatment needed

SECTION 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing media

Extinguishing media: Use water spray to cool containers. Suitable extinguishing media for the surrounding fire should be used.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Extremely flammable. In combustion emits toxic fumes. Fire exposed aerosols should be sprayed with

water to reduce risk of rupture/explosion. Contents of aerosol will add to fuelling of fire.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus.


SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Eliminate all

sources of ignition. If outside keep bystanders upwind and away from danger point.

Page: 2



Revision Number 1 Compilation date: 02/06/15

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Clean-up should be dealt with only by qualified personnel familiar with the specific substance. Refer to

section 13 of SDS for suitable method of disposal.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Handling requirements: Ensure there is sufficient ventilation of the area. Avoid direct contact with the substance.

Smoking is forbidden.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep away from sources of ignition. Keep away from direct sunlight.

Suitable packaging: Not applicable.

7.3. Specific end use(s)

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Hazardous ingredients:

ETHANOL

Workplace exposure limits: Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	1920 mg/m3	-	-	-

BUTANE

UK	1450 mg/m3	1810 mg/m3	-	-
----	------------	------------	---	---

PROPANE

	1	i	ı	
UK	1800 mg/m3	7200 mg/m3	-	-

ISOBUTANE

15050 MAZ					
UK	2400 mg/m3	9600 mg/m3	-	-	

DNEL / PNEC: No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not a source

of ignition.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Protective gloves.

Eye protection: Safety glasses.

Skin protection: Protective clothing.

Environmental: No special requirement.



Revision Number 1 Compilation date: 02/06/15

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance:	Aerosol	
Colour:	Colourless	
Odour:	Pleasant	
Evaporation rate:	Fast	
Oxidising:	Not applicable	
Solubility in water:	Slightly soluble	
Also soluble in:	Most organic solvents	
Viscosity:	Non-viscous	
Boiling point/range°C:	<100	
Flammability limits %: lower:	No data available.	
Flash point°C:	-20	
Autoflammability°C:	No data available.	
Relative density:	Not applicable.	
VOC g/I:	No data available.	
Melting point/range°C:	No data available.	
upper:	No data available.	
Part.coeff. n-octanol/water:	No data available.	
Vapour pressure:	No data available.	
pH:	Not applicable.	

9.2. Other information

Other information: No data available.

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

10.4. Conditions to avoid


Conditions to avoid: Direct sunlight. Heat. Hot surfaces. Sources of ignition. Flames.

10.5. Incompatible materials

Materials to avoid: Strong acids. Strong bases. Strong oxidising agents. Strong reducing agents.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.



Revision Number 1 Compilation date: 02/06/15

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

DERMAL	RBT	LD50	>2000	mg/kg
ORL	MUS	1H LC50	>20	mg/kg
ORL	RAT	LD50	>2000	mg/kg

Toxicity values: No data available.

Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be difficulty swallowing. Headaches or general malaise may result. There may be vomiting and

diarrhoea. The casualty may appear intoxicated. There may be loss of consciousness.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing

or wheezing. Drowsiness or mental confusion may occur. There may be loss of consciousness.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Hazardous ingredients:

ETHANOL

ALGAE	48H EC50	>100	mg/l
Daphnia magna	48H EC50	>100	mg/l
FISH	96H LC50	>100	mg/l

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Soluble in water.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Harmful to aquatic organisms.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

NB: The user's attention is drawn to the possible existence of regional or national regulations

 $regarding\ disposal.$



Revision Number 1 Compilation date: 02/06/15

SECTION 14: TRANSPORT INFORMATION

14.1. UN number UN number: UN1950

14.2. UN proper shipping name Shipping name: AEROSOLS

14.3. Transport hazard class(es)

Transport class: 2

14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous: No

14.6. Special precautions for user Warning: Flammable liquids.

Special precautions: Limited Quantity - 1 Litre/Kilo

Tunnel code: D Transport category: 2

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2 Chemical safety assessment:

SECTION 16: OTHER INFORMATION

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830.

Phrases used in s.2 and s.3: H220: Extremely flammable gas.

H222: Extremely flammable aerosol. H225: Highly flammable liquid and vapour. H229: Pressurised container: May burst if heated

 ${\sf H302: Harmful\ if\ swallowed.}$

H317: May cause an allergic skin reaction. H318: Causes serious eye damage.

H331: Toxic if inhaled.

H372: Causes damage to organs <or state all organs affected, if known> through prolonged or repeated exposure <state route of exposure if it is conclusively proven that no other routes of exposure cause the

hazard>

H410: Very toxic to aquatic life with long lasting effects. H412: Harmful to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be

used only as a guide. This company shall not be held liable for any damage resulting from handling or

from contact with the above product.

^{*} indicates text in the SDS which has changed since the last revision.