







www.meguiars.co.uk

WHICH POLISHER IS BEST?

					
Action type	Orbital	Orbital/Rotating	Orbital/Rotating	Orbital/Rotating	Rotating
Clear coat safe	●●●●●	●●●●●	●●●●●	●●●●●	●●●●●
Performance	●	●●●●●	●●●●●	●●●●●	●●●●●

MEGUIAR'S MT320 FOAM DISCS

Cutting Disc



- Restores faded paint.
- Removes Scratches and Swirls.

Polishing Disc



- Removes holograms and minor swirls.
- Restores gloss.

Finishing Disc



- Perfect disc for wax application.
- Increases paint brilliance.

SOCIAL MEDIA



YouTube
MeguiarsUK



Facebook
MeguiarsUK



Twitter
@MeguiarsUK



Instagram
@MeguiarsUK



Google Plus
MeguiarsUK



PAINT CORRECTION PROCESS

with the MT320 DUAL ACTION POLISHER





PAINT CORRECTION PROCESS

with the MT320 DUAL ACTION POLISHER

BEFORE YOU BEGIN:

Prepare your paint surface by washing the vehicle using a premium car wash such as **Meguiar's® Ultimate Wash & Wax** and **Mircrofibre Wash Mitt**. After washing, dry your vehicle with a **Water Magnet**. If the paint surface feels rough to the touch, we recommend using our **Smooth Surface Clay Kit™** or **Quik Clay Starter Kit™** prior to compounding, polishing, or waxing. For more information on proper washing techniques or using our Smooth Surface Clay Kit please visit our website at www.meguiars.co.uk or contact our **Surface Care Specialists** on 0870 241 6696.



1. Wash your vehicle



2. Clay your vehicle (if needed)

MEGUIAR'S PAINT CORRECTION PROCESS

NEW OR LIKE-NEW PAINT

STEP 1: WAX



- A. Dispense four small dots of **Meguiar's Ultimate Wax** onto a clean **Black Foam DA Finishing Disc (DFF5)**.
- B. Set **MT320 Polisher speed to 3800 OPM**. Apply 2 overlapping passes using light pressure. Apply more product as needed until all painted surfaces of the vehicle are covered in a thin uniform coat.
- C. Wipe off residue with a clean **Meguiar's Supreme® Shine Microfibre Towel**.

AVERAGE PAINT


STEP 1: POLISH



- A. Dispense four small dots of **Meguiar's Ultimate Polish** onto a clean **Yellow Foam DA Polishing Disc (DFP5)**.
- B. Set **MT320 Polisher speed to 4800 OPM**. Work in a 60cm x 60cm section and apply 2 – 3 overlapping passes using moderate pressure. (Do not allow product to dry.)
- C. Wipe off residue using a clean **Meguiar's Supreme Shine Microfibre Towel**.

NEGLECTED PAINT

STEP 1: COMPOUND



- A. Dispense an 'x' shape of **Meguiar's Ultimate Compound** onto a clean **Red Foam Cutting Disc (DFC5)**.
- B. Set **MT320 Polisher speed to 5800 OPM**. Work in a 60cm x 60cm Section and apply 3-4 overlapping passes using moderate pressure, moving the pad slowly across the paint. Re-apply as needed to remove stubborn defects. (Do not allow product to dry.)
- C. Wipe off residue using a clean **Meguiar's Supreme Shine Microfibre Towel**.

STEP 1 SELECT THE CONDITION OF YOUR PAINT




NEW OR LIKE-NEW PAINT

Good gloss, NO swirls or oxidation



AVERAGE PAINT

Light swirls, scratches, or oxidation



NEGLECTED PAINT

Moderate swirls, scratches, oxidation, and stains

STEP 2: WAX



- A. Dispense four small dots of **Meguiar's Ultimate Wax** onto a clean **Black Foam DA Finishing Disc (DFF5)**.
- B. Set **MT320 Polisher speed to 3800 OPM**. Apply 2 overlapping passes using light pressure. Apply more product as needed until all painted surfaces of the vehicle are covered in a thin uniform coat.
- C. Wipe off residue with a clean **Meguiar's Supreme Shine Microfibre Towel**.

ALL DONE!?

Amazed by the results you have just achieved? Don't forget to maintain your show car shine between washes with **Meguiar's Ultimate Quik Detailer**.



STEP 2: POLISH



- A. Dispense four small dots of **Meguiar's Ultimate Polish** onto a clean **Yellow Foam DA Polishing Disc (DFP5)**.
- B. Set **MT320 Polisher speed to 4800 OPM**. Work in a 60cm x 60cm section and apply 2 – 3 overlapping passes using moderate pressure. (Do not allow product to dry.)
- C. Wipe off residue using a clean **Meguiar's Supreme Shine Microfibre Towel**.

STEP 3: WAX



- A. Dispense four small dots of **Meguiar's Ultimate Wax** onto a clean **Black Foam DA Finishing Disc (DFF5)**.
- B. Set **MT320 Polisher speed to 3800 OPM**. Apply 2 overlapping passes using light pressure. Apply more product as needed until all painted surfaces of the vehicle are covered in a thin uniform coat.
- C. Wipe off residue with a clean **Meguiar's Supreme Shine Microfibre Towel**.