

POWER-START...Next Generation Starters






Designed and manufactured in the UK by professionals for professionals



- Various starting solutions for all 12V and 24V vehicles
- Featuring high quality batteries and chargers
- Spike protection
- Audible reverse polarity warning
- On/Off isolator switches
- Fully insulated cable clamps
- Welding grade cables
- Recyclable polyethylene casings
- Full in-house after-sales service



The POWER-START trolley is suitable for the PS-1224HD/PS-24HD and is equipped with 10" high density plastic wheels suitable for all terrain use. The low point of gravity ensures stable and convenient handling

TYPE VEHICLE					
Type POWER-START	Petrol Vehicle 12V	Diesel Vehicle 12V	Light Van/Truck 12V	Truck 24V	Heavy Diesel 24V
PS-510	XX	X			
PS-700	XXX	XXX	XX		
PS-800	XXX	XXX	XXX		
PS-1224	XXX	XXX	XXX	XX	X
PS-1224HD	XXX	XXX	XXX	XXX	XXX
PS-24HD				XXX	XXX

NOTE: Above table is approximate guide only

x = Sufficient, xx = Good, xxx = Excellent

POWER-START TECHNICAL SPECIFICATION

	PS-510	PS-700	PS-800	PS-1224	PS-1224HD	PS-24HD
Voltage	12V DC	12V DC	12V DC	12V+24V DC	12V+24V DC	24V DC
Battery	20Ah	22Ah	2 x 20Ah	2 x 22Ah	2 x 26Ah	2 x 26Ah
Cranking Amps (1)	510	700	800	1200/700	1100/1100	1100
Peak Amps (2)	1200	1600	2400	3500/1600	3500	3500
Cable Clamp	Fully Insulated	Fully Insulated	Fully Insulated	Fully Insulated	Fully Insulated	Fully Insulated
Safety Fuse					500A	500A
Cables	25mm ²	25mm ²	35mm ² /1.7m	35mm ² /1.7m	50mm ² /1.8m	50mm ² /1.8m
Polarity Warning	Yes	Yes	Yes	Yes	Yes	Yes
Spike Protection	Yes	Yes	Yes	Yes	Yes	Yes
Main Switch	Yes	Yes	Yes	Yes	Yes	Yes
Weight	9.5kg	9.5kg	17.5kg	17.9kg	26kg	26kg
Charger	Automatic 2A	Automatic 2A	Automatic 4A	Automatic 4A	Automatic 8A	Automatic 8A

1) The maximum current that can be drawn from a battery during cranking for a specified period of time, at a specified temperature and to a specified end of discharge voltage.

2) The absolute peak instantaneous current measured during a discharge into the equivalent of a short circuit.

Part No.	Single Starts	Multiple Starts
PS510	2.5lt Petrol, 2.0lt Diesels	2.0lt Petrol, 1.6lt Diesels
PS700	3.5lt Petrol, 2.5lt Diesels	3.0lt Petrol, 2.0lt Diesels
PS800	All 12v Vehicles	All 12v Vehicles
PS1224	12v - 2.5lt diesel - 24v - 10lt	12v - 2.0lt diesel - 24v - 8.0lt
PS24HD	All 24v Vehicles	All 24v Vehicles
PS1224HD	12v - 4.0lt diesel - 24v - All	12v - 3.0lt diesel - 24v - All

YOUR DEALER