

# **Power Lock Ultimate Protection**

- Polymer Sealing Blend -

# **Product Description**

Product Category: Protection Category: Standard

Cut: Gloss: -

Polishing Tools: Wax Foam Pad

Microfiber Cloth

#### **Consumer information**

 Long-term sealant for lasting coating preservation and protection Suitable for rotative and eccentric or manual application

 Coating surfaces should be free of residues such as grease or wax. For the best results, clean the surfaces first with Menzerna Control

 After application, allow the product to set and dry completely and then clean with a fresh

microfibre cloth

Menzerna Power Lock Ultimate Protection is the long-lasting polymer coating sealant for all automotive clear coats. PLUP effectively seals the coating surface for long-lasting preservation. Protects against damaging environmental influences while maintaining a brilliant deep gloss.

## Benefits, special features

- Polymer blend
- Long-lasting, maximum protection and ultimate beading effect, resistant against environmental influences
- Protects the vehicle's value

## **Menzerna System**

	Step 1	Step 2	Step 3	Step 4
	Heavy Cut	Medium Cut	Finish	Protection
Standard Process	Heavy Cut Compound 1000 - Pad Use - 22984	Medium Cut Polish 2500 - Classic - 22828	Final Finish 3000 - Classic Swirl Remover - 22029	Power Lock Ultimate Protection 22070

Alternative Products

Heavy Cut Compound 1100

- Wool Use -22930 Medium Cut Polish 2200 - Cut + -

- Cut + -22771

Medium Cut Polish 2400

- Liquid + -22923 Super Finish 3500

- High Gloss Swirl Remover - 22911

Super Finish Plus 3800 - Show Car Finish -

Show Car Finish -22992 Power Protect Ultra 22753

> Sealing Wax Protection 22870

### **Accessories**

Liquid Matt
- Fluid Sanding Cream 22763

Control Cleaner
- Polish Supervision
Spray -

22870

Endless Shine
- Quick Detailing Spray 22747

Metal Polish
- Universal Polishing
Cream 23003

**Volumes** 

Bottle, 250 ml 22070.281.001 Bottle, 1 L 22070.261.001 **Properties** 

Density: 1,0 kg/l Colour: green
Visc: 4-10 Pas Storage: 15-20°C

#### Important notice:

All the information above is based on our empirical values. Please test the use of our product yourself to determine whether it is suitable for your intended application. All matters related to the warranty and liability for this product are governed by our general selling terms and conditions, unless otherwise specified by applicable legal regulations.

#### How to find us:

Menzerna Polishing Compounds
GmbH & Co KG
Industriestrasse 25
D-76470 Ötigheim
Tel.: +49-7222-9157-0
Fax: +49-7222-9157-10
office@menzerna.com