OBLITARATE

Page: 1

Compilation date: 27/03/2014

Revision date: 06/06/2016

Revision No: 2

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: OBLITARATE

Product code: 662

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Company name:	Auto Finesse	
	Unit 7c Silkmead Industrial Estate	
	Buntingford Road, Hare Street	
	Hertfordshire	
	SG9 0DX	
	United Kingdom	
Tel:	08446 93 13 93	
Email:	info@autofinesse.co.uk	

1.4. Emergency telephone number

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP:	Asp. Tox. 1: H304; Aquatic Chronic 2: H411; Flam. Liq. 3: H226; STOT SE 3: H336
Most important adverse effects:	Flammable liquid and vapour. May be fatal if swallowed and enters airways. May cause
	drowsiness or dizziness. Toxic to aquatic life with long lasting effects.

2.2. Label elements

Label elements:	
Hazard statements:	H226: Flammable liquid and vapour.
	H304: May be fatal if swallowed and enters airways.
	H336: May cause drowsiness or dizziness.
	H411: Toxic to aquatic life with long lasting effects.
Hazard pictograms:	GHS02: Flame
	GHS07: Exclamation mark
	GHS08: Health hazard
	GHS09: Environmental



OBLITARATE

Signal words:DangerPrecautionary statements:P210: Keep away from heat, hot surfaces, sparks, open flames and other ignitionsources. No smoking.P241: Use explosion-proof electrical/ventilating/lighting/.. equipment.P301+310: IF SWALLOWED: Immediately call a physician.P303+361+353: IF ON SKIN (or hair): Take off immediately all contaminated clothing.Rinse skin with.P304+340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

HYDROCARBONS, C9-12, N-ALKANES, ISOALKANES, CYCLICS, (2-25%) AROMATICS - REACH registered number (s): 01-2119458049-33-XXXX

EINECS	CAS	PBT / WEL	CLP Classification	Percent
919-446-0	64742-82-1	-	Flam. Liq. 3: H226; STOT SE 3: H336; Asp. Tox. 1: H304; Aquatic Chronic 2: H411; -: EUH066	70-90%

XYLENE

215-535-7	1330-20-7	-	Flam. Liq. 3: H226; Acute Tox. 4: H332;	1-10%
			Acute Tox. 4: H312; Skin Irrit. 2: H315	

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact:	Remove all contaminated clothes and footwear immediately unless stuck to skin.	
	Drench the affected skin with running water for 10 minutes or longer if substance is still	
	on skin. Consult a doctor.	
Eye contact:	Bathe the eye with running water for 15 minutes. Consult a doctor.	
Ingestion:	Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water	
	to drink immediately. Consult a doctor.	
Inhalation:	Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a	
	doctor.	
4.2. Most important symptoms	s and effects, both acute and delayed	
Skin contact:	There may be irritation and redness at the site of contact.	
Eye contact:	There may be irritation and redness. The eyes may water profusely.	
Ingestion:	There may be soreness and redness of the mouth and throat. Nausea and stomach	

pain may occur. There may be vomiting.

Page: 2

OBLITARATE

Page: 3

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray

to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for

disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

Do not handle in a confined space. Avoid the formation or spread of mists in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed. The floor of the

OBLITARATE

Page: 4

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

XYLENE

Workplace exposure limits:		Respirable dust		
State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	220 mg/m3	441 mg/m3	-	-

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures:Ensure there is sufficient ventilation of the area. The floor of the storage room must be
impermeable to prevent the escape of liquids.Respiratory protection:Self-contained breathing apparatus must be available in case of emergency.Hand protection:Impermeable gloves.Eye protection:Safety glasses. Ensure eye bath is to hand.Skin protection:Impermeable protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State:	Liquid		
Colour:	Colourless		
Evaporation rate:	No data available.		
Oxidising:	No data available.		
Solubility in water:	No data available.		
Viscosity:	Non-viscous		
Boiling point/range°C:	>35	Melting point/range°C:	No data available.
Flammability limits %: lower:	No data available.	upper:	No data available.
Flash point°C:	23 - 55	Part.coeff. n-octanol/water:	No data available.
Autoflammability°C:	No data available.	Vapour pressure:	No data available.
Relative density:	~ 0.800	pH:	No data available.
VOC g/I:	800		

9.2. Other information

Other information: No data available.

OBLITARATE

Page: 5

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

XYLENE

ORL	MUS	LD50	2119	mg/kg
ORL	RAT	LD50	4300	mg/kg
SCU	RAT	LD50	1700	mg/kg

Relevant hazards for product:

Hazard	Route	Basis
STOT-single exposure	-	Hazardous: calculated
Aspiration hazard	-	Hazardous: calculated

Symptoms / routes of exposure

Skin contact:	There may be irritation and redness at the site of contact.
Eye contact:	There may be irritation and redness. The eyes may water profusely.
Ingestion:	There may be soreness and redness of the mouth and throat. Nausea and stomach
	pain may occur. There may be vomiting.
Inhalation:	There may be irritation of the throat with a feeling of tightness in the chest.
Delayed / immediate effects:	Immediate effects can be expected after short-term exposure.

OBLITARATE

Page: 6

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: Not biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: Bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Toxic to aquatic organisms. Toxic to soil organisms.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN3295

14.2. UN proper shipping name

Shipping name: HYDROCARBONS, LIQUID, N.O.S.

14.3. Transport hazard class(es)

Transport class: 3

14.4. Packing group

Packing group: III

14.5. Environmental hazards

Environmentally hazardous: Yes

Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D/E

OBLITARATE

Page: 7

Transport category: 3

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Section 16: Other information

Other information	
Other information:	This safety data sheet is prepared in accordance with Commission Regulation (EU) No
	2015/830.
	* indicates text in the SDS which has changed since the last revision.
Phrases used in s.2 and s.3:	EUH066: Repeated exposure may cause skin dryness or cracking.
	H226: Flammable liquid and vapour.
	H304: May be fatal if swallowed and enters airways.
	H312: Harmful in contact with skin.
	H315: Causes skin irritation.
	H332: Harmful if inhaled.
	H336: May cause drowsiness or dizziness.
	H411: Toxic to aquatic life with long lasting effects.
Legal disclaimer:	The above information is believed to be correct but does not purport to be all inclusive
	and shall be used only as a guide. This company shall not be held liable for any
	damage resulting from handling or from contact with the above product.