



SAFETY DATA SHEET

CHIPEX PAINT

Page: 1

Compilation date: 14/02/2014

Revision No: 1

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: CHIPEX PAINT

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Company name: ChipEx Limited
Unit 10
Thorpe Way Industrial Est
Banbury
Oxfordshire
OX16 4SP
Tel: +44 (0)1295 258308
Fax: +44 (0)1295 258308
Email: johnny@chipex.co.uk

1.4. Emergency telephone number

Emergency tel: +44 (0)1295 258308
(office hours only)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CHIP: -: R10; Xn: R20/21/22; Xi: R38; Xi: R41; -: R52/53; -: R66

Classification under CLP: Aquatic Chronic 3: H412; Eye Dam. 1: H318; Flam. Liq. 3: H226; Skin Irrit. 2: H315; STOT SE 3: H336

Most important adverse effects: Flammable. Harmful by inhalation, in contact with skin and if swallowed. Irritating to skin. Risk of serious damage to eyes. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Repeated exposure may cause skin dryness or cracking.

2.2. Label elements

Label elements under CLP:

Hazard statements: H226: Flammable liquid and vapour.
H315: Causes skin irritation.
H318: Causes serious eye damage.
H336: May cause drowsiness or dizziness.
H412: Harmful to aquatic life with long lasting effects.

Signal words: Danger

[cont...]

SAFETY DATA SHEET

CHIPEX PAINT

Page: 2

Hazard pictograms: GHS02: Flame
GHS05: Corrosion
GHS07: Exclamation mark



Precautionary statements: P280: Wear protective gloves/protective clothing/eye protection/face protection.
P303+361+353: IF ON SKIN (or hair): Remove immediately all contaminated clothing. Rinse skin with water/shower.
P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310: Immediately call a POISON CENTER or doctor.
P370+378: In case of fire: Use Use dry chemical, CO2, water spay (fog) or foam for extinction.

Label elements under CHIP:

Hazard symbols: Harmful.



Risk phrases: R10: Flammable.
R20/21/22: Harmful by inhalation, in contact with skin and if swallowed.
R38: Irritating to skin.
R41: Risk of serious damage to eyes.
R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R66: Repeated exposure may cause skin dryness or cracking.

Safety phrases: S2: Keep out of the reach of children.
S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S29: Do not empty into drains.
S36/37/39: Wear suitable protective clothing, gloves and eye / face protection.

2.3. Other hazards

Other hazards: In use, may form flammable / explosive vapour-air mixture.

PBT: This product is not identified as a PBT substance.

Section 3: Composition/information on ingredients

[cont...]

SAFETY DATA SHEET

CHIPEX PAINT

Page: 3

3.2. Mixtures

Hazardous ingredients:

N-BUTYL ACETATE

EINECS	CAS	CHIP Classification	CLP Classification	Percent
204-658-1	123-86-4	-: R10; -: R66; -: R67 Substance with a Community workplace exposure limit.	Flam. Liq. 3: H226; STOT SE 3: H336; -: EUH066	30-50%

BUTAN-1-OL

200-751-6	71-36-3	-: R10; Xn: R22; Xi: R37/38; Xi: R41; -: R67	Flam. Liq. 3: H226; Acute Tox. 4: H302; STOT SE 3: H335; Skin Irrit. 2: H315; Eye Dam. 1: H318; STOT SE 3: H336	1-10%
-----------	---------	--	---	-------

XYLENE

215-535-7	1330-20-7	-: R10; Xn: R20/21; Xi: R38	Flam. Liq. 3: H226; Acute Tox. 4: H332; Acute Tox. 4: H312; Skin Irrit. 2: H315	1-10%
-----------	-----------	-----------------------------	--	-------

2-METHOXY-1-METHYLETHYL ACETATE

203-603-9	108-65-6	-: R10 Substance with a Community workplace exposure limit.	Flam. Liq. 3: H226	1-10%
-----------	----------	--	--------------------	-------

2-METHYLPROPAN-1-OL

201-148-0	78-83-1	-: R10; Xi: R37/38; Xi: R41; -: R67	Flam. Liq. 3: H226; STOT SE 3: H335; Skin Irrit. 2: H315; Eye Dam. 1: H318; STOT SE 3: H336	1-10%
-----------	---------	-------------------------------------	---	-------

LOW BOILING POINT NAPHTHA - UNSPECIFIED - SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM.

265-199-0	64742-95-6	Xn: R65; -: R10; Xi: R37; N: R51/53	Asp. Tox. 1: H304; Flam. Liq. 3: H226; STOT SE 3: H335; Aquatic Chronic 2: H411	1-10%
-----------	------------	-------------------------------------	--	-------

LOW BOILING POINT HYDROGEN TREATED NAPHTHA - NAPHTHA (PETROLEUM), HYDRODESULPHURIZED HEAVY

265-185-4	64742-82-1	Xn: R65; -: R10; N: R51/53	Asp. Tox. 1: H304; Flam. Liq. 3: H226; Aquatic Chronic 2: H411	1-10%
-----------	------------	----------------------------	---	-------

1,2,4-TRIMETHYLBENZENE

202-436-9	95-63-6	-: R10; Xn: R20; Xi: R36/37/38; N: R51/53	Flam. Liq. 3: H226; Acute Tox. 4: H332; Eye Irrit. 2: H319; STOT SE 3: H335; Skin Irrit. 2: H315; Aquatic Chronic 2: H411	<1%
-----------	---------	---	---	-----

MESITYLENE

203-604-4	108-67-8	-: R10; Xi: R37; N: R51/53	Flam. Liq. 3: H226; STOT SE 3: H335; Aquatic Chronic 2: H411	<1%
-----------	----------	----------------------------	---	-----

Section 4: First aid measures

[cont...]

SAFETY DATA SHEET

CHIPEX PAINT

Page: 4

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin.

Drench the affected skin with running water for 10 minutes or longer if substance is still on skin. Consult a doctor.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water to drink immediately. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur. There may be vomiting.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Alcohol or polymer foam. Carbon dioxide. Dry chemical powder. Use water spray to cool containers. Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid. Eliminate all sources of ignition.

[cont...]

SAFETY DATA SHEET

CHIPEX PAINT

Page: 5

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Do not use equipment in clean-up procedure which may produce sparks.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air. Smoking is forbidden. Use non-sparking tools.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed. Keep away from sources of ignition. Prevent the build up of electrostatic charge in the immediate area. Ensure lighting and electrical equipment are not a source of ignition.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

N-BUTYL ACETATE

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	724 mg/m ³ (150ppm)	966 mg/m ³ (200ppm)	-	-

BUTAN-1-OL

UK	-	154 mg/m ³ (50ppm)	-	-
----	---	-------------------------------	---	---

XYLENE

UK	220 mg/m ³ (50ppm)	441 mg/m ³ (100ppm)	-	-
----	-------------------------------	--------------------------------	---	---

[cont...]

SAFETY DATA SHEET

CHIPEX PAINT

Page: 6

2-METHOXY-1-METHYLETHYL ACETATE

UK	274 mg/m ³ (50ppm)	548 mg/m ³ (100ppm)	-	-
----	-------------------------------	--------------------------------	---	---

1,2,4-TRIMETHYLBENZENE

UK	125 mg/m ³	-	-	-
----	-----------------------	---	---	---

MESITYLENE

UK	25 ppm	-	-	-
----	--------	---	---	---

8.1. DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not a source of ignition.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Impermeable gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Impermeable protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Grey

Odour: Characteristic odour

Solubility in water: Insoluble

Boiling point/range°C: >37.78

upper: 11

Relative density: 0.94

Flammability limits %: lower: 1

Flash point°C: 25

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions. Stable at room temperature.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.
Decomposition may occur on exposure to conditions or materials listed below.

[cont...]

SAFETY DATA SHEET

CHIPEX PAINT

Page: 7

10.4. Conditions to avoid

Conditions to avoid: Heat. Hot surfaces. Sources of ignition. Flames.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

N-BUTYL ACETATE

ORL	MUS	LD50	6	gm/kg
ORL	RAT	LD50	10768	mg/kg

BUTAN-1-OL

IVN	RAT	LD50	310	mg/kg
ORL	MUS	LD50	2680	mg/kg
ORL	RAT	LD50	790	mg/kg

XYLENE

ORL	MUS	LD50	2119	mg/kg
ORL	RAT	LD50	4300	mg/kg
SCU	RAT	LD50	1700	mg/kg

2-METHOXY-1-METHYLETHYL ACETATE

IPR	MUS	LD50	750	mg/kg
ORL	RAT	LD50	8532	mg/kg

LOW BOILING POINT NAPHTHA - UNSPECIFIED - SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM.

ORL	RAT	LD50	8400	mg/kg
-----	-----	------	------	-------

1,2,4-TRIMETHYLBENZENE

IPR	RAT	LDLO	1752	mg/kg
ORL	RAT	LD50	5	gm/kg

[cont...]

SAFETY DATA SHEET

CHIPEX PAINT

Page: 8

MESITYLENE

IPR	GPG	LDLO	1303	mg/kg
-----	-----	------	------	-------

Relevant effects for mixture:

Effect	Route	Basis
Acute toxicity (harmful)	INH DRM ING	Hazardous: calculated
Irritation	OPT DRM	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur. There may be vomiting.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

[cont...]

SAFETY DATA SHEET

CHIPEX PAINT

Page: 9

Section 14: Transport information

14.1. UN number

UN number: UN1263

14.2. UN proper shipping name

Shipping name: PAINT

14.3. Transport hazard class(es)

Transport class: 3

14.4. Packing group

Packing group: III

14.5. Environmental hazards

Environmentally hazardous: No

Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D/E

Transport category: 3

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and 3: EUH066: Repeated exposure may cause skin dryness or cracking.

H226: Flammable liquid and vapour.

H302: Harmful if swallowed.

H304: May be fatal if swallowed and enters airways.

H312: Harmful in contact with skin.

H315: Causes skin irritation.

H318: Causes serious eye damage.

H319: Causes serious eye irritation.

H332: Harmful if inhaled.

H335: May cause respiratory irritation.

H336: May cause drowsiness or dizziness.

[cont...]

SAFETY DATA SHEET

CHIPEX PAINT

Page: 10

H411: Toxic to aquatic life with long lasting effects.

H412: Harmful to aquatic life with long lasting effects.

R10: Flammable.

R20/21/22: Harmful by inhalation, in contact with skin and if swallowed.

R20/21: Harmful by inhalation and in contact with skin.

R20: Harmful by inhalation.

R22: Harmful if swallowed.

R36/37/38: Irritating to eyes, respiratory system and skin.

R37/38: Irritating to respiratory system and skin.

R37: Irritating to respiratory system.

R38: Irritating to skin.

R41: Risk of serious damage to eyes.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R65: Harmful: may cause lung damage if swallowed.

R66: Repeated exposure may cause skin dryness or cracking.

R67: Vapours may cause drowsiness and dizziness.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.