



SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Page 1/4

Supernatural Wheel Sealant

Revision 0

Revision date 2012-12-21

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name	Supernatural Wheel Sealant
--------------	----------------------------

1.2. Relevant identified uses of the substance or mixture and uses advised against

Product Use	[SU21] Consumer uses: Private households (= general public = consumers); [PC15] Non-metal-surface treatment products; [AC1] Vehicles; ----- [SU22] Professional uses: Public domain (administration, education, entertainment, services, craftsmen); [PC15] Non-metal-surface treatment products; [AC1] Vehicles;
-------------	---

1.3. Details of the supplier of the safety data sheet

Company	Dodo Juice Limited
Address	Unit 10 Golds Nurseries Business Park Jenkins Drive Elsenham Bishops Stortford CM22 6JX UK
Web	www.dodojuice.com
Telephone	+44(0)1279 813222
Email address of the competent person	factory@dodojuice.com

1.4. Emergency telephone number

Emergency telephone number	+44(0)7891 096802
Company	Dodo Juice Ltd 24 hr

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

2.1.1. Classification - 1999/45/EC	Xn; R22 Symbols: Xn: Harmful.
Main hazards	Harmful if swallowed.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

67/548/EEC / 1999/45/EC

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification
Decamethylcyclopentasiloxane		541-02-6	208-764-9		60 - 70%	Xn; R22 R10
Decamethylcyclohexasiloxane		540-97-6			20 - 30%	Xn; R22 R10

Supernatural Wheel Sealant

Revision 0

Revision date 2012-12-21

SECTION 4: First aid measures**4.1. Description of first aid measures**

Inhalation	Harmful by inhalation. Inhalation may cause nausea and vomiting. May cause dizziness and headache. Move the exposed person to fresh air. Seek medical attention.
Eye contact	May cause irritation to eyes. Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention if irritation or symptoms persist.
Skin contact	May cause irritation to skin. May cause dermatitis. Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist.
Ingestion	Harmful if swallowed. Ingestion may cause nausea and vomiting. Ingestion is irritating to the respiratory tract and may cause damage to the central nervous system. DO NOT INDUCE VOMITING. If swallowed, seek medical advice immediately and show this container or label.

SECTION 5: Firefighting measures**5.1. Extinguishing media**

	Use as appropriate: Carbon dioxide (CO2), Dry chemical, Foam.
--	---

5.2. Special hazards arising from the substance or mixture

	Burning produces irritating, toxic and obnoxious fumes.
--	---

5.3. Advice for firefighters

	Self-contained breathing apparatus. Wear protective clothing.
--	---

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

	Ensure adequate ventilation of the working area. Wear suitable protective equipment.
--	--

6.2. Environmental precautions

	Do not allow product to enter drains. Prevent further spillage if safe.
--	---

6.3. Methods and material for containment and cleaning up

	Absorb with inert, absorbent material. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.
--	---

6.4. Reference to other sections

	See section 8 for further information.
--	--

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

	Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Adopt best Manual Handling considerations when handling, carrying and dispensing.
--	--

7.2. Conditions for safe storage, including any incompatibilities

	Keep in a cool, dry, well ventilated area. Keep containers tightly closed.
--	--

7.3. Specific end use(s)

	No data available.
--	--------------------

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****8.1.1. Exposure Limit Values**

Decamethylcyclopentasiloxane	WEL 8-hr limit ppm: 10	WEL 8-hr limit mg/m3:
	WEL 15 min limit ppm:	WEL 15 min limit mg/m3:

8.2. Exposure controls

8.2.1. Appropriate engineering controls	Ensure adequate ventilation of the working area.
--	--

Supernatural Wheel Sealant

Revision 0

Revision date 2012-12-21

8.2. Exposure controls

Eye / face protection	Approved safety goggles.
Skin protection - Handprotection	Chemical resistant gloves (PVC).

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State	Viscous liquid.
Colour	Clear
Odour	Characteristic
pH	7
Flash point	83 °C
Relative density	0.96 (Water = 1 @ 20 °C)
Autoignition temperature	217 °C
Solubility	Soluble in water

9.2. Other information

	Not applicable.
--	-----------------

SECTION 10: Stability and reactivity

10.1. Reactivity

	Stable under normal conditions.
--	---------------------------------

10.2. Chemical stability

	Stable under normal conditions.
--	---------------------------------

10.3. Possibility of hazardous reactions

	Will not decompose if stored and used as recommended.
--	---

10.4. Conditions to avoid

	Heat.
--	-------

10.5. Incompatible materials

	Strong oxidising agents. Strong acids.
--	--

10.6. Hazardous decomposition products

	Burning produces obnoxious and irritating fumes.
--	--

SECTION 11: Toxicological information

11.1. Information on toxicological effects

	May cause irritation to skin, eyes and mucous membranes.
--	--

11.1.4. Toxicological Information

	No data available
--	-------------------

SECTION 12: Ecological information

12.1. Toxicity

	No data available
--	-------------------

12.2. Persistence and degradability

	Readily biodegradable.
--	------------------------

12.3. Bioaccumulative potential

	Does not bioaccumulate.
--	-------------------------

12.4. Mobility in soil

	Readily absorbed into soil.
--	-----------------------------

12.5. Results of PBT and vPvB assessment

Supernatural Wheel Sealant

Revision 0

Revision date 2012-12-21

12.5. Results of PBT and vPvB assessment

	PBT no.
Further information	
	No Significant Hazard.

SECTION 13: Disposal considerations**General information**

	Dispose of in compliance with all local and national regulations.
Disposal methods	
	Dispose of this material and its container to hazardous or special waste collection point.

SECTION 14: Transport information**ADR/RID**

	The product is not classified as dangerous for carriage.
--	--

IMDG

	The product is not classified as dangerous for carriage.
--	--

IATA

	The product is not classified as dangerous for carriage.
--	--


SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Regulations	REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.
--------------------	---

15.2. Chemical safety assessment

	No data available.
--	--------------------

Labelling

Symbols	The product is classified in accordance with 67/548/EEC. Xn: Harmful. 
Risk phrases	R22 - Harmful if swallowed.

SECTION 16: Other information**Other information**

Text of risk phrases in Section 3	R10 - Flammable R22 - Harmful if swallowed.
--	--

Further information

	The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.
--	--