

Safety Data Sheet

Copyright, 2019, Meguiar's, Inc. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilising Meguiar's, Inc. products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from Meguiar's, Inc., and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group: 28-7685-2 **Version number:** 8.00

Revision date: 25/09/2019 **Supersedes date:** 11/06/2019

Transportation version number: 1.00 (16/08/2011)

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

G182, Ultimate Paste Wax: G18211

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Automotive.

1.3. Details of the supplier of the safety data sheet

Address: Meguiars United Kingdom Limited, 3 Lamport Court, Heartlands, Daventry, Northants, NN11 8UF

Telephone: +44 (0)870 241 6696 E Mail: info@meguiars.co.uk Website: www.meguiars.co.uk

1.4. Emergency telephone number

+44 (0)870 241 6696

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture CLP REGULATION (EC) No 1272/2008

CLASSIFICATION:

Flammable Solid, Category 1 - Flam. Sol. 1; H228

For full text of H phrases, see Section 16.

2.2. Label elements

CLP REGULATION (EC) No 1272/2008

SIGNAL WORD

DANGER.

Symbols:

GHS02 (Flame) |

Pictograms



HAZARD STATEMENTS:

H228 Flammable solid.

PRECAUTIONARY STATEMENTS

General:

P102 Keep out of reach of children.

Prevention:

P210A Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Response:

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water P370 + P378I

or foam to extinguish.

SUPPLEMENTAL INFORMATION:

Supplemental Hazard Statements:

Repeated exposure may cause skin dryness or cracking.

12% of the mixture consists of components of unknown acute oral toxicity.

Contains 12% of components with unknown hazards to the aquatic environment.

Notes on labelling

H304 is not required on the label due to the product's viscosity

Nota P applied to CAS 64741-65-7.

2.3. Other hazards

None known.

SECTION 3: Composition/information on ingredients

Ingredient	CAS Nbr	EC No.	REACH	% by W	t	Classification
			Registration			
			No.			
Hydrocarbons, C11-C13, isoalkanes,		920-901-0		40 -	60	Asp. Tox. 1, H304; EUH066
<2% aromatics						
Siloxanes and silicones, di-Me	63148-62-9			10 -	20	Substance not classified as
						hazardous
2-hydroxyethyl octacosanoate		914-471-3		7 - 1	3	Substance not classified as
						hazardous
Polymer Protectant	Trade			5 - 1	0	Substance with a Community
	Secret					level exposure limit in the
						workplace

Kaolin, calcined	92704-41-1	296-473-8	5 -	10	Substance not classified as hazardous
Hydrocarbons, C12-C16, isoalkanes, cyclics, <2% aromatics		927-676-8	5 -	10	Asp. Tox. 1, H304; EUH066
Silicic acid, sodium salt, reaction products with chlorotrimethylsilane and iso-Pr alc	68988-56-7	273-530-5	1 - :	5	Substance not classified as hazardous
Bodying Agent	Trade Secret		1 - :	5	Substance not classified as hazardous
White Mineral Oil (Petroleum)	8042-47-5	232-455-8	0.1 -	1	Asp. Tox. 1, H304
Naphtha (petroleum), heavy alkylate	64741-65-7	265-067-2	< 0.4		Asp. Tox. 1, H304 - Nota P Aquatic Chronic 2, H411 Flam. Liq. 3, H226; STOT SE 3, H336; EUH066
Titanium dioxide	13463-67-7	236-675-5	< 0.3		Substance with a Community level exposure limit in the workplace

Note: Any entry in the EC# column that begins with the numbers 6, 7, 8, or 9 are a Provisional List Number provided by ECHA pending publication of the official EC Inventory Number for the substance.

Please see section 16 for the full text of any H statements referred to in this section

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Wash with soap and water. If signs/symptoms develop, get medical attention.

Eye contact

Flush eyes with large amounts of water. If signs/symptoms persist, get medical attention.

If swallowed

Rinse mouth. If you are concerned, get medical advice.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1 Information on toxicological effects

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

Substance

Formaldehyde
Carbon monoxide.
Carbon dioxide.
Irritant vapours or gases.

Condition

During combustion.
During combustion.
During combustion.
During combustion.

5.3. Advice for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapours in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible using non-sparking tools. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible.

6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not use in a confined area with minimal air exchange. Keep out of reach of children. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) Wear low static or properly grounded shoes. Use personal protective equipment (eg. gloves, respirators...) as required. To minimize the risk of ignition, determine applicable electrical classifications for the process using this product and select specific local exhaust ventilation equipment to avoid flammable vapour accumulation. Ground/bond container and receiving equipment if there is potential for static electricity accumulation during transfer.

7.2. Conditions for safe storage including any incompatibilities

Store away from heat. Store away from acids. Store away from oxidising agents.

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient CAS Nbr Agency Limit type Additional comments

Titanium oxide 13463-67-7 UK HSC TWA(Inhalable):10

mg/m3;TWA(respirable):4

 mg/m^3

Polymer Protectant Trade Secret UK HSC TWA:2 mg/m3

UK HSC: UK Health and Safety Commission

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

Biological limit values

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

Recommended monitoring procedures:Information on recommended monitoring procedures can be obtained from UK HSC

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment. Use explosion-proof ventilation equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

None required.

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended:

MaterialThickness (mm)Breakthrough TimePolymer laminateNo data availableNo data available

When only incidental contact is anticipated, alternative glove material(s) may be used. If contact with the glove does occur, remove immediately and replace with a set of new gloves. For incidental contact, gloves made of the following material(s) may be used: Nitrile rubber.

Applicable Norms/Standards Use gloves tested to EN 374

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Applicable Norms/Standards

Use a respirator conforming to EN 140 or EN 136: filter types A & P

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state Solid.

Colour Dull Yellow, Soft White

Specific Physical Form:PasteOdorFruity OdorOdour thresholdNo data available.pHNot applicable.

Boiling point/boiling range >= 140.6 °C **Melting point** *Not applicable.*

Flammability (solid, gas) Flammable Solid: Category 1. Flammable Solid: Category 1.

Explosive propertiesOxidising properties
Not classified
Not classified

Flash point >= 93.3 °C [Test Method: Pensky-Martens Closed Cup]

Autoignition temperatureNo data available.Flammable Limits(LEL)No data available.Flammable Limits(UEL)No data available.Vapour pressureNo data available.

Relative density 0.86 [*Ref Std*:WATER=1]

Water solubility Nil

Solubility- non-waterNo data available.Partition coefficient: n-octanol/waterNo data available.Evaporation rateNo data available.Vapour densityNo data available.Decomposition temperatureNo data available.ViscosityNo data available.Density0.86 g/cm3

9.2. Other information

EU Volatile Organic Compounds

No data available.

No data available.

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

Heat

Sparks and/or flames.

10.5 Incompatible materials

Strong acids.

Strong oxidising agents.

10.6 Hazardous decomposition products

Substance

Condition

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from 3M assessments.

11.1 Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

May be harmful if inhaled. May cause additional health effects (see below).

Skin contact

Prolonged or repeated exposure may cause:

Dermal Defatting: Signs/symptoms may include localised redness, itching, drying and cracking of skin.

Eye contact

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion

No known health effects.

Additional Health Effects:

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Acute Toxicity			
Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation- Vapour(4 hr)		No data available; calculated ATE20 - 50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	Inhalation- Vapour		LC50 estimated to be 20 - 50 mg/l
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	Dermal	Rabbit	LD50 > 5,000 mg/kg

Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	Ingestion	Rat	LD50 > 5,000 mg/kg
Siloxanes and silicones, di-Me	Dermal	Rabbit	LD50 > 19,400 mg/kg
Siloxanes and silicones, di-Me	Ingestion	Rat	LD50 > 17,000 mg/kg
2-hydroxyethyl octacosanoate	Dermal		LD50 estimated to be > 5,000 mg/kg
Kaolin, calcined	Dermal		LD50 estimated to be 2,000 - 5,000 mg/kg
2-hydroxyethyl octacosanoate	Ingestion	Rat	LD50 > 2,000 mg/kg
Kaolin, calcined	Ingestion	Rat	LD50 > 2,000 mg/kg
Hydrocarbons, C12-C16, isoalkanes, cyclics, <2% aromatics	Inhalation- Vapour		LC50 estimated to be 20 - 50 mg/l
Hydrocarbons, C12-C16, isoalkanes, cyclics, <2% aromatics	Inhalation- Vapour	Professio nal judgeme nt	LC50 estimated to be 20 - 50 mg/l
Hydrocarbons, C12-C16, isoalkanes, cyclics, <2% aromatics	Dermal	Rabbit	LD50 > 5,000 mg/kg
Hydrocarbons, C12-C16, isoalkanes, cyclics, <2% aromatics	Dermal	Rabbit	LD50 > 5,000 mg/kg
Hydrocarbons, C12-C16, isoalkanes, cyclics, <2% aromatics	Ingestion	Rat	LD50 > 5,000 mg/kg
Hydrocarbons, C12-C16, isoalkanes, cyclics, <2% aromatics	Ingestion	Rat	LD50 > 5,000 mg/kg
Bodying Agent	Dermal		LD50 estimated to be > 5,000 mg/kg
Bodying Agent	Ingestion	Rat	LD50 > 15,000 mg/kg
White Mineral Oil (Petroleum)	Dermal	Rabbit	LD50 > 2,000 mg/kg
White Mineral Oil (Petroleum)	Ingestion	Rat	LD50 > 5,000 mg/kg
Naphtha (petroleum), heavy alkylate	Dermal	Rat	LD50 > 3,000 mg/kg
Naphtha (petroleum), heavy alkylate	Inhalation- Vapour (4 hours)	Rat	LC50 > 9.3 mg/l
Naphtha (petroleum), heavy alkylate	Ingestion	Rat	LD50 > 7,500 mg/kg
Titanium dioxide	Dermal	Rabbit	LD50 > 10,000 mg/kg
Titanium dioxide	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 6.82 mg/l
Titanium dioxide	Ingestion	Rat	LD50 > 10,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	Rabbit	Minimal irritation
Siloxanes and silicones, di-Me	Rabbit	No significant irritation
Hydrocarbons, C12-C16, isoalkanes, cyclics, <2% aromatics	Rabbit	Minimal irritation
White Mineral Oil (Petroleum)	Rabbit	No significant irritation
Naphtha (petroleum), heavy alkylate	Rabbit	Minimal irritation
Titanium dioxide	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	Rabbit	Mild irritant
Siloxanes and silicones, di-Me	Rabbit	No significant irritation
Hydrocarbons, C12-C16, isoalkanes, cyclics, <2% aromatics	Rabbit	Mild irritant
White Mineral Oil (Petroleum)	Rabbit	Mild irritant
Naphtha (petroleum), heavy alkylate	Rabbit	No significant irritation
Titanium dioxide	Rabbit	No significant irritation

Skin Sensitisation

Name	Species	Value
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	Guinea	Not classified
	pig	
Hydrocarbons, C12-C16, isoalkanes, cyclics, <2% aromatics	Guinea	Not classified
	pig	
White Mineral Oil (Petroleum)	Guinea	Not classified
	pig	
Naphtha (petroleum), heavy alkylate	Guinea	Not classified

	pig	
Titanium dioxide	Human	Not classified
	and	
	animal	

Respiratory Sensitisation

For the component/components, either no data is currently available or the data is not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	In Vitro	Not mutagenic
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	In vivo	Not mutagenic
Hydrocarbons, C12-C16, isoalkanes, cyclics, <2% aromatics	In Vitro	Not mutagenic
Hydrocarbons, C12-C16, isoalkanes, cyclics, <2% aromatics	In vivo	Not mutagenic
White Mineral Oil (Petroleum)	In Vitro	Not mutagenic
Naphtha (petroleum), heavy alkylate	In Vitro	Not mutagenic
Naphtha (petroleum), heavy alkylate	In vivo	Not mutagenic
Titanium dioxide	In Vitro	Not mutagenic
Titanium dioxide	In vivo	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	Not	Not	Not carcinogenic
	specified.	available	
Hydrocarbons, C12-C16, isoalkanes, cyclics, <2% aromatics	Not	Not	Not carcinogenic
	specified.	available	
White Mineral Oil (Petroleum)	Dermal	Mouse	Not carcinogenic
White Mineral Oil (Petroleum)	Inhalation	Multiple	Not carcinogenic
		animal	
		species	
Naphtha (petroleum), heavy alkylate	Dermal	Mouse	Some positive data exist, but the data are not
			sufficient for classification
Titanium dioxide	Ingestion	Multiple	Not carcinogenic
		animal	
		species	
Titanium dioxide	Inhalation	Rat	Carcinogenic.

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	Not specified.	Not classified for female reproduction	Not available	NOAEL NA	1 generation
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	Not specified.	Not classified for male reproduction	Not available	NOAEL NA	28 days
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	Not specified.	Not classified for development	Not available	NOAEL NA	during gestation
Hydrocarbons, C12-C16, isoalkanes, cyclics, <2% aromatics	Not specified.	Not classified for female reproduction	Not available	NOAEL NA	1 generation
Hydrocarbons, C12-C16, isoalkanes, cyclics, <2% aromatics	Not specified.	Not classified for female reproduction	Rat	NOAEL Not available	1 generation
Hydrocarbons, C12-C16, isoalkanes, cyclics, <2% aromatics	Not specified.	Not classified for male reproduction	Not available	NOAEL NA	28 days
Hydrocarbons, C12-C16, isoalkanes, cyclics, <2% aromatics	Not specified.	Not classified for male reproduction	Rat	NOAEL Not available	28 days
Hydrocarbons, C12-C16, isoalkanes, cyclics, <2% aromatics	Not specified.	Not classified for development	Not available	NOAEL NA	during gestation
Hydrocarbons, C12-C16, isoalkanes, cyclics, <2% aromatics	Not specified.	Not classified for development	Rat	NOAEL Not available	during gestation
White Mineral Oil (Petroleum)	Ingestion	Not classified for female reproduction	Rat	NOAEL 4,350 mg/kg/day	13 weeks

White Mineral Oil (Petroleum)	Ingestion	Not classified for male reproduction	Rat	NOAEL	13 weeks
				4,350	
				mg/kg/day	
White Mineral Oil (Petroleum)	Ingestion	Not classified for development	Rat	NOAEL	during
		_		4,350	gestation
				mg/kg/day	
Naphtha (petroleum), heavy alkylate	Inhalation	Not classified for development	Rat	NOAEL 900	during
				ppm	organogenesis

Target Organ(s)

Specific Target Organ Toxicity - single exposure

specific ranger organ rowerty single exposure							
Name	Route	Target Organ(s)	Value	Species	Test result	Exposure	
						Duration	
Naphtha (petroleum),	Inhalation	central nervous	May cause drowsiness or	Not	NOAEL Not		
heavy alkylate		system depression	dizziness	available	available		
Naphtha (petroleum),	Inhalation	respiratory irritation	Some positive data exist, but the	Not	NOAEL Not		
heavy alkylate			data are not sufficient for	available	available		
			classification				
Naphtha (petroleum),	Ingestion	central nervous	May cause drowsiness or	Not	NOAEL Not		
heavy alkylate		system depression	dizziness	available	available		

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
White Mineral Oil (Petroleum)	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 1,381 mg/kg/day	90 days
White Mineral Oil (Petroleum)	Ingestion	liver immune system	Not classified	Rat	NOAEL 1,336 mg/kg/day	90 days
Naphtha (petroleum), heavy alkylate	Dermal	bone marrow	Not classified	Rat	NOAEL 2,000 mg/kg/day	4 weeks
Naphtha (petroleum), heavy alkylate	Dermal	hematopoietic system	Not classified	Rat	NOAEL 2,000 mg/kg	4 weeks
Naphtha (petroleum), heavy alkylate	Inhalation	hematopoietic system liver kidney and/or bladder	Not classified	Rat	NOAEL 10.2 mg/l	13 weeks
Naphtha (petroleum), heavy alkylate	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 2,000 mg/kg/day	4 weeks
Titanium dioxide	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 0.01 mg/l	2 years
Titanium dioxide	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure

Aspiration Hazard

Aspiration Hazaru		
Name	Value	
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	Aspiration hazard	
Hydrocarbons, C12-C16, isoalkanes, cyclics, <2% aromatics	Aspiration hazard	
Hydrocarbons, C12-C16, isoalkanes, cyclics, <2% aromatics	Aspiration hazard	
White Mineral Oil (Petroleum)	Aspiration hazard	
Nanhtha (netroleum) heavy alkylate	Asniration hazard	

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient

classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

No product test data available.

Material	CAS#	Organism	Type	Exposure	Test endpoint	Test result
Hydrocarbons, C11-	920-901-0	Green Algae	Estimated	72 hours	Effect Level 50%	>1,000 mg/l
C13, isoalkanes, <2%						
aromatics						
Hydrocarbons, C11-	920-901-0	Rainbow trout	Estimated	96 hours	Lethal Level 50%	>1,000 mg/l
C13, isoalkanes, <2%						
aromatics						
Hydrocarbons, C11-	920-901-0	Water flea	Estimated	48 hours	Effect Level 50%	>1,000 mg/l
C13, isoalkanes, <2%						, ,
aromatics						
Hydrocarbons, C11-	920-901-0	Green Algae	Estimated	72 hours	No obs Effect	1,000 mg/l
C13, isoalkanes, <2%					Level	, ,
aromatics						
Hydrocarbons, C11-	920-901-0	Water flea	Experimental	21 days	No obs Effect	1 mg/l
C13, isoalkanes, <2%				, -	Level	1 8 -
aromatics						
Siloxanes and silicones,	63148-62-9		Data not available			1
di-Me			or insufficient for			
			classification			
Hydrocarbons, C12-	927-676-8	Crustacea other	Estimated	96 hours	Lethal Level 50%	>10,000 mg/l
C16, isoalkanes,	27 070 0	Crustaeva surer) o nours	Ectiliar Development	10,000 mg 1
cyclics, <2% aromatics						
Hydrocarbons, C12-	927-676-8	Green Algae	Estimated	72 hours	Effect Level 50%	>1,000 mg/l
C16, isoalkanes,	27 070 0	Green ringue	Estimated	/2 Hours	Effect Ecver 5070	1,000 mg/1
cyclics, <2% aromatics						
Hydrocarbons, C12-	927-676-8	Green Algae	Estimated	72 hours	Effect Level 50%	>1,000 mg/l
C16, isoalkanes,)2/ 0/00	Green Angue	Estimated	/2 nours	Effect Ecvel 5070	1,000 mg/1
cyclics, <2% aromatics						
Hydrocarbons, C12-	927-676-8	Green Algae	Estimated	72 hours	No obs Effect	1,000 mg/l
C16, isoalkanes,)2/ 0/00	Green Angue	Estimated	/2 Hours	Level	1,000 mg/1
cyclics, <2% aromatics					Level	
Hydrocarbons, C12-	927-676-8	Rainbow trout	Estimated	96 hours	Lethal Level 50%	>1,000 mg/l
C16, isoalkanes,)2/ 0/00	Rumoow trout	Estimated) o nours	Ectilal Level 3070	1,000 mg/1
cyclics, <2% aromatics						
Hydrocarbons, C12-	927-676-8	Water flea	Estimated	48 hours	Effect Level 50%	>1,000 mg/l
C16, isoalkanes,)2/ 0/00	Water fied	Estimated	40 Hours	Effect Ecvel 5070	1,000 mg/1
cyclics, <2% aromatics						
Hydrocarbons, C12-	927-676-8	Rainbow trout	Experimental	96 hours	Lethal Level 50%	>88,444 mg/l
C16, isoalkanes,	1727-070-0	Kambow trout	Experimental	70 Hours	Lettiai Level 5070	> 00,444 mg/1
cyclics, <2% aromatics						
Hydrocarbons, C12-	927-676-8	Water flea	Experimental	48 hours	Effect Level 50%	>1,000 mg/l
C16, isoalkanes,)2/ 0/00	Water fied	Experimental	40 Hours	Effect Ecvel 5070	1,000 mg/1
cyclics, <2% aromatics						
Hydrocarbons, C12-	927-676-8	Green Algae	Estimated	72 hours	No obs Effect	1,000 mg/l
C16, isoalkanes,)2/ 0/00	Green Angue	Estimated	/2 nours	Level	1,000 mg/1
cyclics, <2% aromatics					Ec ver	
Hydrocarbons, C12-	927-676-8	Water flea	Experimental	21 days	No obs Effect	1 mg/l
C16, isoalkanes,	1,2,0,00	Tracer from	Zaperinientui		Level	19 1
cyclics, <2% aromatics					120.00	
Hydrocarbons, C12-	927-676-8	Water flea	Experimental	21 days	No obs Effect	1 mg/l
C16, isoalkanes,	1 2, 0,00	1. 4.0. 1104			Level	
cyclics, <2% aromatics					120.00	
Kaolin, calcined	92704-41-1	Green algae	Estimated	72 hours	EC50	2,500 mg/l
, caronica		Joseph uigue		-		_,_ ,_ ,,, ,
Kaolin, calcined	92704-41-1	Water flea	Estimated	48 hours	EC50	>100 mg/l
, caronica		1. 4.0. 1104				· · · · · · · · · · · · · · · · · · ·
Kaolin, calcined	92704-41-1	Zebra Fish	Estimated	96 hours	LC50	>100 mg/l
, •	[]	2000011011			12000	
Į	1		ı	1		I .

Kaolin, calcined	92704-41-1	Green algae	Estimated	72 hours	Effect	41 mg/l
					Concentration 10%	
Kaolin, calcined	92704-41-1	Rainbow trout	Estimated	30 days	NOEC	>100 mg/l
Polymer Protectant	Trade Secret		Data not available or insufficient for classification			
Bodying Agent	Trade Secret	Zebra Fish	Experimental	96 hours	LC50	>500 mg/l
Silicic acid, sodium salt, reaction products with chlorotrimethylsilane and iso-Pr alc	68988-56-7		Data not available or insufficient for classification			
White Mineral Oil (Petroleum)	8042-47-5	Water flea	Estimated	48 hours	Effect Level 50%	>100 mg/l
White Mineral Oil (Petroleum)	8042-47-5	Bluegill	Experimental	96 hours	Lethal Level 50%	>100 mg/l
White Mineral Oil (Petroleum)	8042-47-5	Green algae	Estimated	72 hours	No obs Effect Level	>100 mg/l
White Mineral Oil (Petroleum)	8042-47-5	Water flea	Estimated	21 days	No obs Effect Level	>100 mg/l
Naphtha (petroleum), heavy alkylate	64741-65-7		Data not available or insufficient for classification			
Titanium dioxide	13463-67-7	Diatom	Experimental	72 hours	EC50	>10,000 mg/l
Titanium dioxide	13463-67-7	Fathead minnow	Experimental	96 hours	LC50	>100 mg/l
Titanium dioxide	13463-67-7	Water flea	Experimental	48 hours	EC50	>100 mg/l
Titanium dioxide	13463-67-7	Diatom	Experimental	72 hours	NOEC	5,600 mg/l

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	920-901-0	Estimated Biodegradation	28 days	BOD	31.3 % BOD/ThBOD	OECD 301F - Manometric respirometry
Siloxanes and silicones, di- Me	63148-62-9	Data not availbl- insufficient			N/A	
Hydrocarbons, C12-C16, isoalkanes, cyclics, <2% aromatics	927-676-8	Estimated Biodegradation	28 days	BOD	31.3 % BOD/ThBOD	OECD 301F - Manometric respirometry
Hydrocarbons, C12-C16, isoalkanes, cyclics, <2% aromatics	927-676-8	Experimental Biodegradation	28 days	BOD	22 % BOD/ThBOD	OECD 301F - Manometric respirometry
Kaolin, calcined	92704-41-1	Data not availbl- insufficient			N/A	
Polymer Protectant	Trade Secret	Data not availbl- insufficient			N/A	
Bodying Agent	Trade Secret	Data not availbl- insufficient			N/A	
Silicic acid, sodium salt, reaction products with chlorotrimethylsilane and iso-Pr alc	68988-56-7	Data not availbl- insufficient			N/A	
White Mineral Oil (Petroleum)	8042-47-5	Experimental Biodegradation	28 days	CO2 evolution	0 % weight	OECD 301B - Modified sturm or CO2
Naphtha (petroleum), heavy alkylate	64741-65-7	Estimated Photolysis		Photolytic half-life (in air)	<4.01 days (t 1/2)	Other methods
Naphtha (petroleum), heavy alkylate	64741-65-7	Experimental Biodegradation	28 days	BOD	8-22 % weight	OECD 301D - Closed bottle test
Titanium dioxide	13463-67-7	Data not availbl- insufficient			N/A	

12.3 : Bioaccumulative potential

Material	Cas No.	Test type	Duration	Study Type	Test result	Protocol
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	920-901-0	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Siloxanes and silicones, di- Me	63148-62-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Hydrocarbons, C12-C16, isoalkanes, cyclics, <2% aromatics	927-676-8	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Hydrocarbons, C12-C16, isoalkanes, cyclics, <2% aromatics	927-676-8	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Kaolin, calcined	92704-41-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Polymer Protectant	Trade Secret	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Bodying Agent	Trade Secret	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Silicic acid, sodium salt, reaction products with chlorotrimethylsilane and iso-Pr alc	68988-56-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
White Mineral Oil (Petroleum)	8042-47-5	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Naphtha (petroleum), heavy alkylate	64741-65-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Titanium dioxide	13463-67-7	Experimental BCF- Carp	42 days	Bioaccumulation factor	9.6	Other methods

12.4. Mobility in soil

Please contact manufacturer for more details

12.5. Results of the PBT and vPvB assessment

This material does not contain any substances that are assessed to be a PBT or vPvB

12.6. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

 $Dispose\ of\ contents/\ container\ in\ accordance\ with\ the\ local/regional/national/international\ regulations.$

Incinerate in a permitted waste incineration facility. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of the manufacturer, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/CE and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional

regulations are complied with and always use a licensed waste contractor

EU waste code (product as sold)

20 01 13* Solvents

SECTION 14: Transportation information

ADR: UN1325 Flammable Solid, Organic, N.O.S. (Hydrotreated Heavy Naphtha (Petroleum) and Hydrotreated Light Petroleum Distillates); 4,1; II; (E); F1

IATA: UN1325 Flammable Solid, Organic, N.O.S. (Hydrotreated Heavy Naphtha (Petroleum) and Hydrotreated Light Petroleum Distillates); 4,1; II

IMDG: UN1325 Flammable Solid, Organic, N.O.S. (Hydrotreated Heavy Naphtha (Petroleum) and Hydrotreated Light Petroleum Distillates); 4,1; II; FA, SG

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Carcinogenicity

<u>Ingredient</u>	CAS Nbr	<u>Classification</u>	Regulation
Titanium dioxide	13463-67-7	Grp. 2B: Possible human	International Agency
		carc.	for Research on Cancer

15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out for this mixture. Chemical safety assessments for the contained substances may have been carried out by the registrants of the substances in accordance with Regulation (EC) No 1907/2006, as amended.

SECTION 16: Other information

List of relevant H statements

EUH066	Repeated exposure may cause skin dryness or cracking.
H226	Flammable liquid and vapour.
H228	Flammable solid.
H304	May be fatal if swallowed and enters airways.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

Revision information:

Section 1: Product name information was modified.

Label: CLP Classification information was modified.

Label: CLP Environmental Hazard Statements information was deleted.

Label: CLP Percent Unknown information was modified.

Label: CLP Precautionary - Disposal information was deleted.

Section 3: Composition/Information of ingredients table information was modified.

Section 4: First aid for ingestion (swallowing) information information was modified.

Section 8: Eye protection information information was added.

Section 8: Eye/face protection information information was deleted.

Section 8: glove data value information was modified.

Section 8: Occupational exposure limit table information was modified.

Section 8: Personal Protection - Eye information information was deleted.

Section 8: Personal Protection - Skin/hand information information was modified.

Section 08: Skin protection - incidental contact text information was added.

Section 08: Skin protection - incidental contact information was added.

Section 09: Color information was added.

Section 09: Odor information was added.

Sections 3 and 9: Odour, colour, grade information information was deleted.

Section 11: Acute Toxicity table information was modified.

Section 11: Aspiration Hazard Table information was modified.

Section 11: Carcinogenicity Table information was modified.

Section 11: Germ Cell Mutagenicity Table information was modified.

Section 11: Health Effects - Ingestion information information was modified.

Section 11: Health Effects - Inhalation information information was modified.

Section 11: Reproductive Toxicity Table information was modified.

Section 11: Serious Eye Damage/Irritation Table information was modified.

Section 11: Skin Corrosion/Irritation Table information was modified.

Section 11: Skin Sensitization Table information was modified.

Section 11: Target Organs - Repeated Table information was modified.

Section 11: Target Organs - Single Table information was modified.

Section 12: Component ecotoxicity information information was modified.

Section 12: Persistence and Degradability information information was modified.

Section 12:Bioccumulative potential information information was modified.

Section 15: Regulations - Inventories information was deleted.

Two-column table displaying the unique list of H Codes and statements (std phrases) for all components of the given material. information was modified.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

Meguiar's, Inc. United Kingdom SDSs are available at www.meguiars.co.uk