



Printing date 23.07.2019 Version number 5 Revision: 23.07.2019

- SECTION 1: Identification of the substance/mixture and of the company/ undertaking
 - · 1.1 Product identifier
 - · Trade name: Super Heavy Cut Compound 300
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Abrasive and polishing compound
- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

Menzerna Polishing Compounds GmbH & Co. KG Industriestraße 25 76470 ÖTIGHEIM GERMANY

sds@menzerna.com Tel.: +49 (0) 7222 9157-0

- · Further information obtainable from: Product and Environmental Safety Department
- 1.4 Emergency telephone number: CHEMTREC: +1 703-741-5970 / 1-800-424-9300 CCN 842438

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



GHS08 health hazard

STOT RE 2 H373 May cause damage to the central nervous system through prolonged or repeated exposure. Route of exposure: Inhalation.

Aguatic Chronic 3 H412 Harmful to aguatic life with long lasting effects.

- · 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms



GHS08

- Signal word Warning
- · Hazard-determining components of labelling:

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

· Hazard statements

H373 May cause damage to the central nervous system through prolonged or repeated exposure. Route of exposure: Inhalation.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P273 Avoid release to the environment.

P314 Get medical advice/attention if you feel unwell.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 2)





Printing date 23.07.2019 Version number 5 Revision: 23.07.2019

Trade name: Super Heavy Cut Compound 300

(Contd. of page 1)

· Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

- 2.3 Other hazards
- · Results of PBT and vPvB assessment
- PBT: Not applicable.vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- **Description:** Mixture: consisting of the following components.

· Dangerous components:		
CAS: 64742-55-8 EINECS: 265-158-7 Reg.nr.: 01-2119487077-29	Distillates (petroleum), hydrotreated light paraffinic	5-20%
EC number: 919-164-8 Reg.nr.: 01-2119473977-17	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) STOT RE 1, H372; Asp. Tox. 1, H304; Aquatic Chronic 3, H412	≥2.5-<10%
EC number: 918-811-1 Reg.nr.: 01-2119463583-34	Hydrocarbons, C10, aromatics, <1% naphthalene Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H336	2.5-10%

Additional information:

Distillates (petroleum), hydrotreated light paraffinic: DMSO Extract < 3% according Method IP 346 For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing:

Rinse out mouth and then drink plenty of water.

If symptoms persist consult doctor.

· 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

Treat according to symptoms.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: Water spray, foam, dry powder or carbon dioxide.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture Nitrogen oxides (NOx)

(Contd. on page 3)





Printing date 23.07.2019 Version number 5 Revision: 23.07.2019

Trade name: Super Heavy Cut Compound 300

(Contd. of page 2)

- 5.3 Advice for firefighters
- · Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Ensure adequate ventilation. Use personal protection recommended in section 8.

6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- · Information about fire and explosion protection: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store in a well-ventilated place. Storage temperature: between 5°C and 30°C.

- Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: None.
- · Storage class: 10
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

· 8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· DNELs		
Hydrocarbons, C10, aromatics, <1% naphthalene		alene
Oral	DNEL, general population, oral	7.5 mg/kg KG/Tag
Dermal	DNEL, general population, dermal	7.5 mg/kg KG/Tag

(Contd. on page 4)





Printing date 23.07.2019 Version number 5 Revision: 23.07.2019

Trade name: Super Heavy Cut Compound 300

		(Contd. of page 3)
	DNEL, worker, dermal	12.5 mg/kg KG/Tag
Inhalative	DNEL, general population, inhalativ	32 mg/m3
	DNEL, worker, inhalativ	150 mg/m3

- Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Respiratory protection:

Use suitable respiratory protective device only when aerosol or mist is formed.

Filter A/P2

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protection of hands:



Protective gloves

Normally one does not come into direct contact with the product during use. At the risk of entanglement of protective glove in rotating or linear moving machine parts protective gloves should not be worn. Recommendation for short-term exposure: Use chemical resistant gloves.

Material of gloves

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.45 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

≥ 480 min

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection: Safety glasses

pH-value at 20 °C (68 °F):

· Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties General Information Appearance: Form: Colour: Odour: Odour: Odour threshold: 9.1 Information on basic physical and chemical properties Viscous White Characteristic Not determined.

7-10

(Contd. on page 5)





Printing date 23.07.2019 Version number 5 Revision: 23.07.2019

Trade name: Super Heavy Cut Compound 300

	(Contd. of page
 Change in condition Melting point/freezing point: Initial boiling point and boiling range 	Undetermined. : >100 °C (>212 °F)
· Flash point:	>100 °C (>212 °F)
· Flammability (solid, gas):	Not applicable.
· Decomposition temperature:	Not determined.
· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product does not present an explosion hazard.
· Explosion limits: Lower: Upper: · Oxidising properties	Not determined. Not determined. Not determined.
· Vapour pressure:	Not determined.
Density at 20 °C (68 °F): Relative density Vapour density Evaporation rate	1-1.3 g/cm³ (8.35-10.85 lbs/gal) Not determined. Not determined. Not determined.
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity: Dynamic: Kinematic at 40 °C (104 °F):	Not determined. >20.5 mm²/s
Solvent content: VOC (EC) 9.2 Other information	13,5-14,0 % No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity None under normal conditions.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

(Contd. on page 6)





Printing date 23.07.2019 Version number 5 Revision: 23.07.2019

Trade name: Super Heavy Cut Compound 300

(Contd. of page 5)

· LD/LC50 v	LD/LC50 values relevant for classification:		
CAS: 647	CAS: 64742-55-8 Distillates (petroleum), hydrotreated light paraffinic		
Oral	LD50	>5,000 mg/kg (rat)	
Dermal	LD50	>2,000 mg/kg (rabbit)	
Hydrocar	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)		
Oral	LD50	>5,000 mg/kg (rat)	
Dermal	LD50	>3,400 mg/kg (rabbit)	
Hydrocar	Hydrocarbons, C10, aromatics, <1% naphthalene		
Oral	LD50	>5,000 mg/kg (rat)	
Dermal	LD50	>2,000 mg/kg (rabbit)	
Inhalative	LC50/4 h	>4,688 mg/l (rat)	

- Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure

May cause damage to the central nervous system through prolonged or repeated exposure. Route of exposure: Inhalation.

· Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:		
Hydrocarbons, C10, aromatics, <1% naphthalene		
EL50 (48h)	3-10 mg/l (daphnia)	
EL50 (72h)	11 mg/l (Pseudokirchneriella subcapitata)	
LL50 (96h)	2-5 mg/l (Oncorhynchus mykiss)	
NOELR (72h)	2.5 mg/l (Pseudokirchneriella subcapitata)	

- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- General notes:

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

- 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.

(Contd. on page 7)





Printing date 23.07.2019 Version number 5 Revision: 23.07.2019

Trade name: Super Heavy Cut Compound 300

(Contd. of page 6)

- · vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Must be specially treated adhering to official regulations.

Waste disposal key:

Waste codes should be determined in consultation with the customer, supplier and disposal.

- · Uncleaned packaging:
- Recommendation:

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

SECTION 14: Transport information

 14.1 UN-Number ADR, ADN, IMDG, IATA 14.2 UN proper shipping name ADR, ADN, IMDG, IATA 14.3 Transport hazard class(es) ADR, ADN, IMDG, IATA Class 14.4 Packing group ADR, IMDG, IATA Void 14.5 Environmental hazards: Not applicable. 14.6 Special precautions for user 	<u></u>	
· ADR, ADN, IMDG, IATA Void · 14.3 Transport hazard class(es) · ADR, ADN, IMDG, IATA · Class Void · 14.4 Packing group · ADR, IMDG, IATA Void · 14.5 Environmental hazards: Not applicable.		Void
· ADR, ADN, IMDG, IATA · Class Void · 14.4 Packing group · ADR, IMDG, IATA Void · 14.5 Environmental hazards: Not applicable.		Void
Class Void 14.4 Packing group ADR, IMDG, IATA Void 14.5 Environmental hazards: Not applicable.	· 14.3 Transport hazard class(es)	
· ADR, IMDG, IATA Void · 14.5 Environmental hazards: Not applicable.		Void
**		Void
· 14.6 Special precautions for user Not applicable.	· 14.5 Environmental hazards:	Not applicable.
• •	· 14.6 Special precautions for user	Not applicable.
· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable.		
· UN "Model Regulation": Void	· UN "Model Regulation":	Void

SECTION 15: Regulatory information

• 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture Regulation 1907/2006/EC, REACH concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals.

Regulation 453/2010/EU, REACH as amended.

Regulation 1272/2008/EC, on Classification, Labelling and Packaging of substances and mixtures.

- Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.





Printing date 23.07.2019 Version number 5 Revision: 23.07.2019

Trade name: Super Heavy Cut Compound 300

(Contd. of page 7)

SECTION 16: Other information

The details of the safety data sheet apply only to the product described in the context of its intended use. The information is based on the current state of our knowledge. It is intended to describe our product in view of the risks posed by it and the relevant precautionary measures. It does not represent an assurance of product and quality characteristics. The information in this safety data sheet is required under Article 31 and Annex II of Regulation EC (VO) no. 1907/2006.

· Relevant phrases

H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness.

H372 Causes damage to the central nervous system through prolonged or repeated exposure. Route of exposure: Inhalation.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

· Department issuing SDS: Product and Environmental Safety Department

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

* Data compared to the previous version altered.

EU -