NANOLEX EX NEW

Page: 1

Compilation date: 20.04.2020

Revision No: 1

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: NANOLEX EX NEW

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC9a: Coatings and paints, thinners, paint removers.

1.3. Details of the supplier of the safety data sheet

Company name: Infinitec GmbH

Matzenberg 171 Saarbrücken D-66115 Germany Tel: +4968198 800306

Email: a.neuner@infinitec-gmbh.de

1.4. Emergency telephone number

Emergency tel: Medical Emergency information in case of poisoning: Poison Information Center Mainz -24h - Phone: +49 (0) 6131 19240 (advisory service in German or English language)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP:	Aquatic Chronic 3: H412; Asp. Tox. 1: H304; Flam. Liq. 3: H226; -: EUH208
Most important adverse effects:	Contains orange terpenes. May produce an allergic reaction. Flammable liquid and
	vapour. May be fatal if swallowed and enters airways. Harmful to aquatic life with long
	lasting effects.

2.2. Label elements

Label elements:Hazard statements:EUH208: Contains orange terpenes. May produce an allergic reaction.H226: Flammable liquid and vapour.H304: May be fatal if swallowed and enters airways.H412: Harmful to aquatic life with long lasting effects.Hazard pictograms:GHS02: FlameGHS08: Health hazard



Signal words: Danger

NANOLEX EX NEW

 Precautionary statements:
 P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

 P241: Use explosion-proof equipment.
 P280: Wear protective gloves/protective clothing/eye protection/face protection.

 P301+P310: IF SWALLOWED: Immediately call a POISON CENTER or doctor.
 P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing.

 Rinse skin with water .
 P331: Do NOT induce vomiting.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

LOW BOILING POINT HYDROGEN TREATED NAPHTHA - NAPHTHA (PETROLEUM), HYDROTREATED HEAVY

EINECS	CAS	PBT / WEL	CLP Classification	Percent
265-150-3	64742-48-9	-	Asp. Tox. 1: H304; Flam. Liq. 3: H226	60.000%

HYDROCARBONS, C10-C12, ISO ALKANES, <2% AROMATICS

-	923-037-2	-	Flam. Liq. 3: H226; Asp. Tox. 1: H304; Aquatic Chronic 2: H411	10.000%

HYDROCARBONS, C11-C12, ISOALKANES, <2% AROMATICS

-	90622-58-5	-	Asp. Tox. 1: H304	10.000%
HYDROCARBO	NS, C11-C13, I	SOALKANES, <2% AROMATICS		

Asp. Tox. 1: H304

N-BUTYL ACETATE

204-658-1	123-86-4	-	Flam. Liq. 3: H226; STOT SE 3: H336;	4.000%
			-: EUH066	

ORANGE TERPENES

-	8028-48-6	-	Flam. Liq. 3: H226; Resp. Sens. 1:	0.800%
			H334; Aquatic Acute 1: H400; Aquatic	
			Chronic 1: H410; Skin Irrit. 2: H315;	
			Skin Sens. 1: H317	

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes.

Ingestion: Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water

to drink immediately. Transfer to hospital as soon as possible.

10.000%

NANOLEX EX NEW

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be soreness and redness of the mouth and throat. There may be difficulty swallowing. Nausea and stomach pain may occur. There may be vomiting.

Inhalation: Absorption through the lungs can occur causing symptoms similar to those of ingestion.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray

to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

NANOLEX EX NEW

7.1. Precautions for safe handling

Handling requirements: Avoid the formation or spread of mists in the air. Avoid direct contact with the substance.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

N-BUTYL ACETATE

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	724 mg/m3	966 mg/m3	-	-

DNEL/PNEC Values

Hazardous ingredients:

ORANGE TERPENES

Туре	Exposure	Value	Population	Effect
DNEL	Oral	4,44 mg/kg bw/day	General Population	Systemic
DNEL	Dermal	8,89 mg/kg bw/day	Workers	Systemic
DNEL	Dermal	4,44 mg/kg bw/day	General Population	Systemic
DNEL	Inhalation	31,1 mg/m3	Workers	Systemic
DNEL	Inhalation	7,78 mg/m3	General Population	Systemic
PNEC	Fresh water	0,0054 mg/l	-	-
PNEC	Marine water	0,00054 mg/ml	-	-
PNEC	Microorganisms in sewage treatment	2,1 mg/l	-	-
PNEC	Soil (agricultural)	0,261 mg/kg dw	-	-
PNEC	Fresh water	1,3 mg/kg dw	-	-
PNEC	Marine water	0,12 mg/kg dw	-	-

8.2. Exposure controls

Respiratory protection: Respiratory protection not required.

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

NANOLEX EX NEW

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Viscosity: Non-viscous

Flash point°C: 41

VOC g/l: 980

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

HYDROCARBONS, C10-C12, ISO ALKANES, <2% AROMATICS

DERMAL	RBT	LD50	>5000	mg/kg
ORAL	RAT	LD50	>5000	mg/kg

HYDROCARBONS, C11-C12, ISOALKANES, <2% AROMATICS

DERMAL	RBT	LD50	>5000	mg/kg
ORAL	RAT	LD50	>5000	mg/kg

NANOLEX EX NEW

Page: 6

HYDROCARBONS, C11-C13, ISOALKANES, <2% AROMATICS

DERMAL	RAT	LD50	>5000	mg/kg
ORAL	RAT	LD50	>5000	mg/kg
VAPOURS	RAT	4H LC50	>5	mg/kg

N-BUTYL ACETATE

ORL RAT LD50 10768 mg/kg	
--	--

ORANGE TERPENES

DERMAL	RBT	LD50	>5000	mg/kg
ORAL	RAT	LD50	4,400	mg/kg

Relevant hazards for product:

Hazard	Route	Basis
Aspiration hazard	-	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be soreness and redness of the mouth and throat. There may be difficulty swallowing. Nausea and stomach pain may occur. There may be vomiting.

Inhalation: Absorption through the lungs can occur causing symptoms similar to those of ingestion.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

HYDROCARBONS, C10-C12, ISO ALKANES, <2% AROMATICS

Daphnia magna	48H EC50	1000	mg/l
RAINBOW TROUT (Oncorhynchus mykiss)	96H LC50	1000	mg/l

ORANGE TERPENES

ALGAE	72H ErC50	150	μΙ/Ι
Daphnia magna	48H EC50	0,42	mg/l
FISH	96H LC50	0,72	mg/l

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

NANOLEX EX NEW

Page: 7

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1993

14.2. UN proper shipping name

Shipping name: FLAMMABLE LIQUID, N.O.S. (LOW BOILING POINT HYDROGEN TREATED NAPHTHA - NAPHTHA (PETROLEUM), HYDROTREATED HEAVY; HYDROCARBONS, C10-C12, ISO ALKANES, <2% AROMATICS; N-BUTYL ACETATE; ORANGE TERPENES)

14.3. Transport hazard class(es)

Transport class: 3

14.4. Packing group

Packing group: |||

14.5. Environmental hazards

Environmentally hazardous: No

Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D/E

Transport category: 3

NANOLEX EX NEW

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information

 (EU) 2015/830 * indicates text in the SDS which has changed since the last revision. Phrases used in s.2 and s.3: EUH066: Repeated exposure may cause skin dryness or cracking. EUH208: Contains <name of="" sensitising="" substance="">. May produce an allergic reaction.</name> H226: Flammable liquid and vapour.
Phrases used in s.2 and s.3: EUH066: Repeated exposure may cause skin dryness or cracking. EUH208: Contains <name of="" sensitising="" substance="">. May produce an allergic reaction. H226: Flammable liquid and vapour.</name>
EUH208: Contains <name of="" sensitising="" substance="">. May produce an allergic reaction. H226: Flammable liquid and vapour.</name>
H226: Flammable liquid and vapour.
H304: May be fatal if swallowed and enters airways.
H315: Causes skin irritation.
H317: May cause an allergic skin reaction.
H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H336: May cause drowsiness or dizziness.
H400: Very toxic to aquatic life.
H410: Very toxic to aquatic life with long lasting effects.
H411: Toxic to aquatic life with long lasting effects.
H412: Harmful to aquatic life with long lasting effects.
Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive
and shall be used only as a guide. This company shall not be held liable for any
damage resulting from handling or from contact with the above product.